

屋内照明器具特性	
品番 (品名)	NNN7 1 5 0 4
光源	NNU140155LE9 ×1 1610.0 l m
管理番号	K0133662 (0) DR 1
BZ分類	BZ1 / 3.5 / BZ2 / 8.5 / BZ1

器具効率		86 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01)																Z C M
保守率		良 中 否	0.81	0.6	63	56	51	48	62	56	51	48	61	55	51	48	60	54	51	48	47
			0.77	0.8	70	64	59	56	69	63	59	56	68	62	59	56	66	61	58	56	54
			0.68	1.0	74	69	64	61	73	68	64	61	72	67	64	61	70	66	63	61	59
				1.25	78	73	69	66	77	72	69	66	75	71	68	65	73	70	67	65	63
下方投影面積		cm ²		1.5	80	76	72	69	79	75	72	69	77	74	71	68	76	73	70	68	66
			等価発光面積	cm ²	2.0	83	80	77	74	82	79	76	74	80	77	75	73	79	76	74	72
取付 高さ	器具間隔最大限			2.5	85	82	79	77	84	81	79	77	82	80	78	76	80	78	77	75	73
	横方向 (A) 縦方向 (B)			3.0	87	84	81	79	86	83	81	79	84	81	80	78	82	80	78	77	75
H m	1.00 H m	1.00 H m		4.0	88	86	84	82	87	85	83	82	85	83	82	81	83	82	81	79	77
				5.0	89	87	86	84	88	86	85	84	86	85	83	82	84	83	82	81	79
				7.0	90	89	88	86	89	88	87	86	87	86	85	84	85	84	84	83	81
				10.0	91	90	89	88	90	89	88	87	88	87	87	86	86	86	85	84	82

