

屋内照明器具特性	
品番 (品名)	L G W5 1 7 7 9 W
光源	LLD4000LCB1 ×1 845.0 l m
管理番号	K0182069 (0) DR 1
B Z 分類	BZ5 / 1.1 / BZ4 / 6.0 / BZ5 / 8.5 / BZ4

器具効率		63 %	反射率	天井	80 %				70 %				50 %				30 %				0 %			
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %			
				床	10 %				10 %				10 %				10 %				0 %			
上方光束		0 %	室指数	照明率 (X0.01)																		Z	C	M
下方光束		63 %																						
保守率		良 中 否	0.63	0.6	36	29	24	20	36	28	24	20	34	28	23	20	33	27	23	20	19			
			0.6	0.8	43	36	31	27	42	35	30	27	40	34	30	27	39	33	30	27	25			
			0.56	1.0	47	40	35	32	46	40	35	32	44	39	35	32	42	38	34	31	30			
				1.25	51	45	40	37	50	44	40	36	48	43	39	36	46	42	39	36	34			
下方投影面積		c m ²		1.5	53	48	44	40	52	47	43	40	50	46	42	40	49	45	42	39	38			
等価発光面積			c m ²	2.0	57	52	49	45	56	52	48	45	54	50	47	45	52	49	46	44	43			
				2.5	59	55	52	49	58	54	51	49	56	53	50	48	54	52	50	48	46			
取付 高さ	器具間隔最大限		3.0	60	57	54	52	60	56	54	51	58	55	53	51	56	54	52	50	48				
	横方向 (A)			縦方向 (B)		4.0	62	60	57	55	61	59	57	55	60	58	56	54	58	56	55	53	52	
H m	1.23 H m		1.23 H m		5.0	64	61	59	58	63	61	59	57	61	59	58	56	59	58	57	55	54		
					7.0	65	63	62	60	64	63	61	60	62	61	60	59	61	60	59	58	56		
					10.0	66	65	64	63	65	64	63	62	64	63	62	61	62	61	61	60	58		

