

屋内照明器具特性	
品番 (品名)	XAD3 1 0 0 V
光源	LLD4000VCS1 ×1 830.0 lm
管理番号	K0181856 (0) DR 1
BZ分類	BZ4 / 0.7 / BZ3

器具効率		76 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01)																Z C M
保守率		良 中 否	0.67	0.6	46	38	33	29	46	38	32	29	44	37	32	29	42	36	32	28	27
			0.63	0.8	54	46	41	37	53	46	41	37	51	45	40	37	49	44	40	37	35
			0.56	1.0	59	52	47	43	58	51	46	43	56	50	46	42	54	49	45	42	41
			1.25	63	57	52	48	62	56	52	48	60	55	51	48	58	54	50	47	46	
下方投影面積		cm ²	1.5	66	60	56	52	65	60	56	52	63	58	55	52	61	57	54	51	50	
			等価発光面積	cm ²	2.0	70	65	61	58	69	65	61	58	67	63	60	57	65	62	59	57
取付高さ	器具間隔最大限		2.5	72	68	65	62	71	68	64	62	69	66	63	61	67	65	62	60	59	
	横方向 (A) 縦方向 (B)		3.0	74	71	68	65	73	70	67	65	71	68	66	64	69	67	65	63	61	
H m	1.20 H m	1.20 H m	4.0	76	73	71	69	75	73	70	68	73	71	69	67	71	69	68	66	64	
			5.0	77	75	73	71	76	74	72	71	74	73	71	70	72	71	70	68	66	
			7.0	79	77	76	74	78	76	75	73	76	75	73	72	74	73	72	71	69	
			10.0	80	79	77	76	79	78	77	76	77	76	75	74	75	74	74	73	71	

