

屋内照明器具特性	
品番 (品名)	XLGB3302
光源	LLD4000LCS1 ×1 830.0 lm
管理番号	K0181864 (0) DR 1
BZ分類	BZ5

器具効率		83 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01)																ZCM
保守率		良 中 否	0.67	0.6	47	37	31	27	46	37	31	26	44	36	30	26	42	35	30	26	24
			0.63	0.8	55	46	40	35	54	45	39	35	52	44	38	34	49	43	38	34	32
			0.56	1.0	61	52	46	41	59	51	45	41	57	50	44	40	54	48	43	40	38
				1.25	66	58	52	47	64	57	51	47	61	55	50	46	58	53	49	45	43
下方投影面積		cm ²		1.5	69	62	56	51	67	61	55	51	64	59	54	50	62	57	53	49	47
			等価発光面積	cm ²	2.0	73	67	62	58	72	66	61	57	69	64	60	56	66	62	58	55
取付 高さ	器具間隔最大限			2.5	76	71	66	62	75	70	65	62	72	67	64	61	69	65	62	60	57
	横方向 (A) 縦方向 (B)			3.0	78	74	69	66	77	72	69	65	74	70	67	64	71	68	65	63	60
H m	1.26 H m	1.26 H m		4.0	81	77	74	71	79	76	73	70	76	73	71	68	74	71	69	67	64
				5.0	82	79	76	74	81	78	75	73	78	75	73	71	75	73	71	70	67
				7.0	84	82	80	77	83	80	78	76	80	78	76	75	77	76	74	73	70
				10.0	86	84	82	81	84	83	81	79	81	80	79	77	79	78	77	76	72

