

~~ランプ光束1000 1m~~

非常点灯時の照度 (30 分後)

ランバ光束 1000 μm



品番	K1 - LSS9 - 2 - 15 (XDL211AGN)				
名称					
光源	LED5000 / 98 / 665				
管理番号	K0176558 (2) DR 1				
光束	665.0 l m * 1.00			備考	非常点灯時の照度 (30分後)
保守率	0.93				

非常灯配置表

器具取付高さ (m)		2.1	2.2	2.3	2.4	2.5	2.6	2.7	2.8	2.9	3.0	3.1	3.2	3.3	3.4	3.5	3.6
単体配置	A1	5.4	5.5	5.6	5.7	5.8	5.8	5.9	5.9	6.0	6.0	6.0	6.0	5.9	5.8	5.6	5.3
	B1	5.5	5.6	5.7	5.8	5.9	6.0	6.0	6.1	6.1	6.2	6.1	6.1	6.0	5.9	5.8	5.7
	B' 1	4.9	5.0	5.1	5.2	5.3	5.3	5.4	5.4	5.4	5.4	5.4	5.3	5.3	5.1	5.0	4.9
直線配置	A2	12.6	13.0	13.3	13.6	13.9	14.1	14.4	14.7	14.9	15.1	15.3	15.5	15.6	15.8	16.0	16.2
	B2	12.1	12.5	12.8	13.1	13.4	13.7	13.9	14.2	14.5	14.7	14.9	15.1	15.3	15.4	15.6	15.8
四角配置	A4	11.2	11.4	11.7	11.8	12.1	12.2	12.5	12.6	13.0	13.0	13.3	13.4	13.5	13.8	13.9	14.1
	B4	10.6	10.9	11.1	11.5	11.7	12.1	12.2	12.6	12.6	13.0	13.0	13.4	13.6	13.7	14.0	14.1
壁からの距離 (最大)	A0	3.5	3.6	3.7	3.7	3.7	3.6	3.7	3.6	3.8	3.7	3.8	3.7	3.6	3.6	3.6	3.6
	B0	2.9	3.0	3.1	3.2	3.2	3.3	3.3	3.4	3.4	3.5	3.4	3.5	3.5	3.4	3.6	3.5

器具取付高さ (m)		3.7	3.8	3.9	4.0	4.1	4.2	4.3	4.4	4.5							
単体配置	A1	5.2	5.0	4.8	4.7	4.5	4.3	4.2	----	----							
	B1	5.6	5.5	5.4	5.4	5.3	5.3	5.2	----	----							
	B' 1	4.8	4.7	4.6	4.5	4.4	4.3	4.2	----	----							
直線配置	A2	16.3	16.4	16.5	16.6	16.7	16.6	16.5	16.3	16.1							
	B2	15.9	16.0	16.0	16.1	16.1	16.1	16.1	16.0	15.9							
四角配置	A4	14.3	14.4	14.6	14.7	14.9	15.0	15.2	15.4	15.4							
	B4	14.3	14.4	14.5	14.7	14.8	15.0	15.1	15.2	15.4							
壁からの距離 (最大)	A0	3.5	3.5	3.4	3.3	3.2	3.1	3.0	1.0	1.0							
	B0	3.5	3.5	3.4	3.5	3.4	3.4	3.3	1.0	1.0							

器具取付高さ (m)																	
単体配置																	
直線配置																	
四角配置																	
壁からの距離 (最大)																	