

屋内照明器具特性	
品番 (品名)	LGB52016
光源	LGB52016 ×1 1700.0 l m
管理番号	K0131231 (1) DB 1
BZ分類	BZ5

器具効率	100%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	9%	床	10%				10%				10%				10%				0%	
下方光束	91%	室指数	照明率 ( X0.01 )																ZCM	
保守率	良	0.63	0.6	5.5	4.3	3.5	3.0	5.4	4.2	3.5	3.0	5.0	4.0	3.4	2.9	4.7	3.9	3.3	2.9	2.6
	中	0.6	0.8	6.5	5.4	4.6	4.0	6.3	5.2	4.5	4.0	5.9	5.0	4.4	3.9	5.6	4.8	4.2	3.8	3.5
	否	0.56	1.0	7.2	6.1	5.3	4.7	6.9	5.9	5.2	4.7	6.5	5.7	5.1	4.6	6.1	5.4	4.9	4.5	4.1
			1.25	7.7	6.8	6.0	5.5	7.5	6.6	5.9	5.4	7.1	6.3	5.7	5.2	6.7	6.0	5.5	5.1	4.8
下方投影面積	c m <sup>2</sup>		1.5	8.1	7.3	6.6	6.0	7.9	7.1	6.4	5.9	7.5	6.8	6.2	5.8	7.0	6.5	6.0	5.6	5.2
等価発光面積	c m <sup>2</sup>		2.0	8.7	7.9	7.3	6.8	8.5	7.8	7.2	6.7	8.0	7.4	6.9	6.5	7.6	7.1	6.7	6.3	5.9
取付高さ	器具間隔最大限		2.5	9.0	8.4	7.8	7.4	8.8	8.2	7.7	7.3	8.3	7.8	7.4	7.0	7.9	7.5	7.1	6.8	6.4
	横方向 (A)	縦方向 (B)	3.0	9.3	8.7	8.2	7.8	9.0	8.5	8.1	7.7	8.6	8.2	7.8	7.4	8.2	7.8	7.5	7.2	6.7
1.5m	1.95 m	2.05 m	4.0	9.6	9.1	8.7	8.4	9.4	8.9	8.6	8.2	8.9	8.6	8.2	8.0	8.5	8.2	7.9	7.7	7.2
2	2.57	2.6	5.0	9.8	9.4	9.1	8.7	9.6	9.2	8.9	8.6	9.1	8.8	8.5	8.3	8.7	8.4	8.2	8.0	7.5
2.5	3.2	3.18	7.0	10.0	9.7	9.5	9.2	9.8	9.5	9.3	9.0	9.3	9.1	8.9	8.7	8.9	8.7	8.6	8.4	7.9
3	3.82	3.77	10.0	10.2	10.0	9.8	9.6	10.0	9.8	9.6	9.4	9.5	9.4	9.2	9.1	9.1	9.0	8.8	8.7	8.2

