

# 屋内照明器具特性

品番 (品名)	L G W 8 0 2 5 5	
光源	LED2700_70_315 ×1	315.0 l m
管理番号	K0136363 ( 0 ) DB 1	
B Z 分類	B Z 5	

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %	
			70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10		
上方光束	10 %	反射率	10 %				10 %				10 %				10 %				0 %	
下方光束	90 %		壁	10 %				10 %				10 %				10 %				0 %
		床	10 %				10 %				10 %				10 %				0 %	
		室指数	照明率 ( X 0.01 )																Z C M	
保守率	良 0.63	0.6	0.6	56	44	36	31	54	43	36	30	51	41	34	30	48	39	33	29	27
	中 0.6	0.6	0.8	65	54	46	40	63	53	45	40	59	50	44	39	56	48	42	38	35
	否 0.56	0.6	1.0	72	61	53	48	69	60	53	47	65	57	51	46	62	55	49	45	42
下方投影面積	c m <sup>2</sup>	1.25	78	68	61	55	75	66	59	54	71	63	57	53	67	60	55	51	48	
		1.5	82	73	66	61	79	71	65	60	75	68	63	58	71	65	60	56	53	
等価発光面積	c m <sup>2</sup>	2.0	87	80	74	69	85	78	72	68	80	74	70	66	76	71	67	64	60	
		2.5	91	84	79	74	88	82	77	73	84	79	74	71	79	75	72	69	64	
取付高さ	器具間隔最大限		3.0	93	87	83	78	91	85	81	77	86	82	78	75	82	78	75	72	68
	横方向 ( A )	縦方向 ( B )	4.0	96	91	87	84	94	89	86	82	89	86	82	80	85	82	79	77	72
H m	0.00 H m	0.00 H m	5.0	98	94	91	88	95	92	89	86	91	88	85	83	87	84	82	80	75
			7.0	100	97	94	92	98	95	93	90	93	91	89	87	89	87	85	84	79
			10.0	102	100	98	96	99	97	96	94	95	93	92	90	91	89	88	87	82

