

# 屋内照明器具特性

品番 (品名)	LGB87080K	
光源	LDA3L-H-E17/25E/W ×1	360.0 l m
管理番号	K0123530(0)DB1	
BZ分類	BZ4/0.9/BZ5/6.0/BZ6	

器具効率	83 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
上方光束	22 %	室指数	床	10 %				10 %				10 %				10 %				0 %
下方光束	61 %		照明率 ( X0.01 ) ZCM																	
保守率	良 中 否	0.67 0.63 0.56	0.6	46	36	30	26	44	35	29	26	40	32	28	24	36	30	26	23	20
			0.8	53	44	37	33	50	42	36	32	45	39	34	30	41	36	31	28	25
			1.0	57	49	43	38	54	47	41	37	49	43	38	35	44	39	35	32	28
			1.25	62	54	48	43	59	51	46	42	53	47	43	39	48	43	39	36	32
下方投影面積 等価発光面積	c m <sup>2</sup> c m <sup>2</sup>	1.5 2.0 2.5	1.5	65	57	52	47	61	55	50	45	56	50	46	42	50	46	42	39	34
			2.0	69	62	57	53	65	60	55	51	59	55	51	48	54	50	47	44	38
			2.5	71	66	61	57	68	63	59	55	62	58	54	51	56	53	50	47	41
取付 高さ H m	器具間隔最大限		3.0	73	68	64	60	70	66	62	58	64	60	57	54	58	55	52	50	43
	横方向 (A)	縦方向 (B)																		
	1.09 H m	1.10 H m	4.0	76	72	68	65	72	69	66	63	66	63	60	58	60	57	55	53	46
			5.0	77	74	71	68	74	71	68	65	67	65	63	61	61	59	57	56	48
			7.0	79	77	74	72	76	73	71	69	69	67	66	64	63	62	60	59	51
			10.0	81	79	77	75	77	76	74	72	71	69	68	67	65	63	62	61	53

