

屋内照明器具特性	
品番 (品名)	L G W C 8 0 4 1 6
光源	LED2700_70_273 x1 273.0 lm
管理番号	K0160293(0)DR1
BZ分類	BZ10

器具効率	100%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	50%	床	10%				10%				10%				10%				0%	
下方光束	50%	室指数	照明率 (X0.01)																ZCM	
保守率	良	0.63	0.6	4.3	3.0	2.2	1.6	3.9	2.7	2.0	1.5	3.2	2.2	1.6	1.2	2.5	1.8	1.3	0.9	0.4
	中	0.6	0.8	5.1	3.8	2.9	2.3	4.6	3.5	2.7	2.1	3.7	2.8	2.2	1.7	2.9	2.2	1.7	1.3	0.7
	否	0.56	1.0	5.7	4.4	3.6	2.9	5.2	4.1	3.3	2.6	4.2	3.3	2.7	2.2	3.3	2.6	2.1	1.7	0.9
			1.25	6.2	5.1	4.2	3.5	5.7	4.6	3.8	3.2	4.6	3.8	3.2	2.7	3.6	3.0	2.5	2.1	1.2
下方投影面積		cm ²	1.5	6.6	5.6	4.7	4.0	6.1	5.1	4.3	3.7	4.9	4.2	3.6	3.1	3.9	3.3	2.9	2.5	1.4
等価発光面積		cm ²	2.0	7.2	6.3	5.5	4.8	6.6	5.7	5.0	4.4	5.4	4.8	4.2	3.7	4.3	3.8	3.4	3.0	1.8
取付高さ	器具間隔最大限		2.5	7.6	6.7	6.0	5.4	7.0	6.2	5.6	5.0	5.8	5.2	4.6	4.2	4.6	4.2	3.8	3.4	2.2
	横方向 (A)	縦方向 (B)	3.0	7.9	7.1	6.4	5.9	7.2	6.5	5.9	5.4	6.0	5.5	5.0	4.6	4.8	4.4	4.1	3.7	2.4
Hm	0.00Hm	0.00Hm	4.0	8.3	7.6	7.0	6.5	7.6	7.0	6.5	6.0	6.3	5.9	5.5	5.1	5.2	4.8	4.5	4.2	2.8
			5.0	8.5	7.9	7.4	7.0	7.8	7.3	6.9	6.5	6.6	6.2	5.8	5.5	5.4	5.1	4.8	4.5	3.0
			7.0	8.8	8.3	7.9	7.5	8.1	7.7	7.4	7.0	6.8	6.5	6.2	6.0	5.6	5.4	5.2	4.9	3.4
			10.0	9.0	8.7	8.4	8.1	8.4	8.1	7.8	7.5	7.1	6.8	6.6	6.4	5.9	5.7	5.5	5.3	3.7

