

# 屋内照明器具特性

品番 (品名)	XLX110UEV									
光源	LED3500_85_11170 ×1 11170.0 1m									
管理番号	K0154865(8)D 1									
BZ分類	BZ5/0.9/BZ4									

器具効率	100%	天井	80%				70%				50%				30%				0%				
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%		
				床	10%				10%				10%				10%				0%		
上方光束	0%	室指数	照明率 (X0.01)																				ZCM
下方光束	100%																						
保守率	良 中 否	0.81	0.6	57	45	38	32	56	45	37	32	54	44	37	32	52	43	36	32	30			
		0.77	0.8	68	56	49	43	66	56	48	43	64	54	48	43	61	53	47	42	40			
			1.0	74	64	57	51	73	63	56	51	70	62	55	50	67	60	55	50	48			
		0.68	1.25	81	71	64	59	79	70	64	58	76	69	63	58	73	67	62	58	55			
下方投影面積	c m <sup>2</sup>	1.5	85	76	70	64	83	75	69	64	80	73	68	64	77	72	67	63	61				
		2.0	90	83	78	73	89	82	77	73	86	80	76	72	83	78	74	71	69				
等価発光面積	c m <sup>2</sup>	2.5	94	88	83	79	92	87	82	78	89	85	81	77	87	83	79	76	74				
		3.0	96	91	87	83	95	90	86	82	92	88	84	81	89	86	83	80	78				
取付高さ	器具間隔最大限		4.0	99	95	92	89	98	94	91	88	95	92	89	87	93	90	88	85	83			
	横方向 (A)	縦方向 (B)	5.0	101	98	95	92	100	97	94	91	97	95	92	90	95	92	90	89	86			
1.5m	1.94m	1.93m	7.0	103	101	99	97	102	100	98	96	99	97	96	94	97	95	94	92	90			
2	2.56	2.56	10.0	105	103	101	100	103	102	100	99	101	100	98	97	99	98	96	95	93			
2.5	3.17	3.17																					
3	3.81	3.8																					

