

# 屋内照明器具特性

品番 (品名)	XLX160REN									
光源	LED5000_85_6500 x1 6500.0lm									
管理番号	K0154865(8)D1									
BZ分類	BZ5/0.9/BZ4									

器具効率	100%	天井	80%				70%				50%				30%				0%			
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%		
上方光束	0%	反射率	10%				10%				10%				10%				0%			
下方光束	100%		床	10%				10%				10%				10%				0%		
室指数	照明率 (X0.01) ZCM																					
保守率	良 中 否	0.81	0.6	5.7	4.5	3.8	3.2	5.6	4.5	3.7	3.2	5.4	4.4	3.7	3.2	5.2	4.3	3.6	3.2	3.0		
		0.77	0.8	6.8	5.6	4.9	4.3	6.6	5.6	4.8	4.3	6.4	5.4	4.8	4.3	6.1	5.3	4.7	4.2	4.0		
		0.68	1.0	7.4	6.4	5.7	5.1	7.3	6.3	5.6	5.1	7.0	6.2	5.5	5.0	6.7	6.0	5.5	5.0	4.8		
			1.25	8.1	7.1	6.4	5.9	7.9	7.0	6.4	5.8	7.6	6.9	6.3	5.8	7.3	6.7	6.2	5.8	5.5		
下方投影面積			cm <sup>2</sup>																			
等価発光面積			cm <sup>2</sup>																			
取付高さ	器具間隔最大限		2.5	9.4 8.8 8.3 7.9 9.2 8.7 8.2 7.8 8.9 8.5 8.1 7.7 8.7 8.3 7.9 7.6 7.4																		
	横方向 (A)	縦方向 (B)		3.0	9.6 9.1 8.7 8.3 9.5 9.0 8.6 8.2 9.2 8.8 8.4 8.1 8.9 8.6 8.3 8.0 7.8																	
1.5m	1.92m	1.91m	4.0	9.9 9.5 9.2 8.9 9.8 9.4 9.1 8.8 9.5 9.2 8.9 8.7 9.3 9.0 8.8 8.5 8.3																		
2	2.54	2.53	5.0	10.1 9.8 9.5 9.2 10.0 9.7 9.4 9.1 9.7 9.5 9.2 9.0 9.5 9.2 9.0 8.9 8.6																		
2.5	3.17	3.17	7.0	10.3 10.1 9.9 9.7 10.2 10.0 9.8 9.6 9.9 9.7 9.6 9.4 9.7 9.5 9.4 9.2 9.0																		
3	3.81	3.8	10.0	10.5 10.3 10.1 10.0 10.3 10.2 10.0 9.9 10.1 10.0 9.8 9.7 9.9 9.8 9.6 9.5 9.3																		

