

屋内照明器具特性

品番 (品名)	L G W 8 0 2 6 4	
光源	LED2700_70_263 ×1	263.0 l m
管理番号	K0160972 (0) DB 1	
B Z 分類	B Z 8 / 0 . 7 / B Z 7 / 0 . 9 / B Z 6 / 4 . 5 / B Z 5	

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
上方光束	6 %	床	10 %				10 %				10 %				10 %				0 %	
下方光束	94 %	室指数	照明率 (X 0 . 0 1)																Z C M	
保守率	良	0.63	0.6	4.8	3.4	2.5	1.9	4.6	3.3	2.4	1.8	4.3	3.1	2.4	1.8	4.0	3.0	2.3	1.8	1.5
	中	0.6	0.8	5.8	4.5	3.6	2.9	5.6	4.4	3.5	2.9	5.2	4.2	3.4	2.8	4.9	4.0	3.3	2.7	2.4
	否	0.56	1.0	6.6	5.3	4.4	3.7	6.3	5.2	4.3	3.7	5.9	4.9	4.2	3.6	5.5	4.7	4.0	3.5	3.2
			1.25	7.2	6.1	5.2	4.5	7.0	5.9	5.1	4.5	6.6	5.7	4.9	4.4	6.2	5.4	4.8	4.3	3.9
下方投影面積		cm ²	1.5	7.7	6.7	5.9	5.2	7.5	6.5	5.8	5.1	7.1	6.2	5.6	5.0	6.6	5.9	5.4	4.9	4.5
等価発光面積		cm ²	2.0	8.4	7.5	6.8	6.2	8.2	7.3	6.7	6.1	7.7	7.0	6.4	5.9	7.3	6.7	6.2	5.8	5.4
取付高さ	器具間隔最大限		2.5	8.8	8.1	7.4	6.9	8.6	7.9	7.3	6.8	8.1	7.5	7.0	6.6	7.7	7.2	6.8	6.4	6.0
	横方向 (A)	縦方向 (B)	3.0	9.1	8.4	7.9	7.4	8.9	8.3	7.7	7.3	8.4	7.9	7.5	7.1	8.0	7.6	7.2	6.9	6.5
H m	0.00 H m	0.00 H m	4.0	9.5	8.9	8.5	8.0	9.3	8.8	8.3	7.9	8.8	8.4	8.0	7.7	8.4	8.1	7.8	7.5	7.1
			5.0	9.7	9.3	8.8	8.5	9.5	9.1	8.7	8.3	9.1	8.7	8.4	8.1	8.7	8.4	8.1	7.9	7.4
			7.0	10.0	9.6	9.3	9.0	9.8	9.4	9.2	8.9	9.4	9.1	8.8	8.6	9.0	8.8	8.6	8.4	7.9
			10.0	10.2	9.9	9.7	9.5	10.0	9.7	9.5	9.3	9.6	9.4	9.2	9.0	9.2	9.0	8.9	8.7	8.3

