

# 屋内照明器具特性

品番 (品名)	LGB52684														
光源	LED3500_70_2270 x1 2270.0 1m														
管理番号	K0140348(0)DB1														
BZ分類	BZ5														

器具効率	100%	天井	80%				70%				50%				30%				0%		
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
				床	10%				10%				10%				10%				0%
上方光束 下方光束	7% 93%	室指数	照明率 ( X0.01) ZCM																		
保守率	良 中 否 0.63 0.6 0.56	0.6	5.6	4.3	3.6	3.0	5.4	4.3	3.5	3.0	5.1	4.1	3.4	2.9	4.8	3.9	3.3	2.9	2.7		
		0.8	6.5	5.4	4.6	4.0	6.3	5.3	4.5	4.0	6.0	5.1	4.4	3.9	5.7	4.9	4.3	3.8	3.6		
		1.0	7.2	6.1	5.3	4.8	7.0	6.0	5.3	4.7	6.6	5.7	5.1	4.6	6.2	5.5	5.0	4.5	4.2		
		1.25	7.8	6.8	6.1	5.5	7.6	6.6	6.0	5.4	7.1	6.4	5.8	5.3	6.8	6.1	5.6	5.2	4.9		
下方投影面積 等価発光面積	c m <sup>2</sup> c m <sup>2</sup>	1.5	8.2	7.3	6.6	6.0	8.0	7.1	6.5	6.0	7.5	6.8	6.3	5.8	7.1	6.6	6.1	5.7	5.3		
		2.0	8.7	8.0	7.4	6.8	8.5	7.8	7.2	6.8	8.1	7.5	7.0	6.6	7.7	7.2	6.8	6.4	6.0		
		2.5	9.1	8.4	7.9	7.4	8.9	8.3	7.7	7.3	8.4	7.9	7.5	7.1	8.0	7.6	7.2	6.9	6.5		
取付 高さ	器具間隔最大限		3.0	9.3	8.7	8.3	7.8	9.1	8.6	8.1	7.7	8.7	8.2	7.8	7.5	8.3	7.9	7.6	7.3	6.9	
	横方向 (A) H m	縦方向 (B) 1.25 H m	4.0	9.6	9.2	8.8	8.4	9.4	9.0	8.6	8.3	9.0	8.6	8.3	8.0	8.6	8.3	8.0	7.8	7.4	
			5.0	9.8	9.4	9.1	8.8	9.6	9.3	8.9	8.6	9.2	8.9	8.6	8.4	8.8	8.6	8.3	8.1	7.7	
			7.0	10.1	9.8	9.5	9.2	9.8	9.6	9.3	9.1	9.4	9.2	9.0	8.8	9.0	8.9	8.7	8.5	8.1	
			10.0	10.2	10.0	9.8	9.6	10.0	9.8	9.6	9.5	9.6	9.5	9.3	9.1	9.2	9.1	9.0	8.8	8.4	

