

屋内照明器具特性

品番 (品名)	LGWJ 50129K															
光源	LED2700_70_85 x1 85.0 lm															
管理番号	K0158846(0)DB1															
BZ分類	BZ10															

器具効率	100%	天井	80%				70%				50%				30%				0%			
	上方光束		54%	反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
	下方光束		46%		床	10%				10%				10%				10%				0%
室指数	照明率 (X0.01) ZCM																					
保守率	良	0.63	0.6	0.56	0.6	41	28	20	14	37	25	18	12	29	20	14	9	22	15	10	6	0
	中	0.6	0.6	0.6	0.6	48	35	26	19	43	31	23	17	34	24	18	13	25	18	13	9	1
	否	0.56	0.56	0.56	0.56	53	40	31	23	48	36	27	21	37	28	21	16	28	21	15	11	2
下方投影面積 等価発光面積	cm ²	1.25	1.5	2.0	2.5	58	45	36	28	52	41	32	25	41	32	25	19	30	23	18	13	3
		2.0	2.5	3.0	4.0	62	50	40	32	55	44	36	29	43	35	28	22	32	26	20	16	5
		3.0	4.0	5.0	6.0	67	56	47	39	60	50	42	35	47	40	33	27	36	29	24	20	7
取付高さ	器具間隔最大限		m	m	m	2.5	3.0	4.0	5.0	6.0	7.0	8.0	9.0	10.0	11.0	12.0	13.0	14.0	15.0	16.0	17.0	18.0
	横方向 (A)	縦方向 (B)				71	60	52	44	64	55	47	40	51	43	37	31	38	32	27	23	9
1.5m	0	0	0	0	4.0	77	69	62	55	70	63	56	50	56	50	45	40	43	39	34	30	15
2	0	0	0	0	5.0	80	72	66	60	73	66	60	54	59	53	48	44	46	41	37	34	18
2.5	0	0	0	0	7.0	83	77	72	66	76	70	65	61	62	57	53	49	49	45	42	39	22
3	0	0	0	0	10.0	86	81	77	72	79	74	70	66	65	61	58	55	52	49	46	43	26

