

# 屋内照明器具特性

|         |                                  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
|---------|----------------------------------|--|--|--|--|--|--|--|--|--|--|--|--|--|--|
| 品番 (品名) | LGB15077Z                        |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| 光源      | LDA4L-H-E17/E/S/W/2 ×1 440.0 1 m |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| 管理番号    | K0123326(0)DB1                   |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| BZ分類    | BZ4/0.7/BZ3                      |  |  |  |  |  |  |  |  |  |  |  |  |  |  |

|        |                 |               |      |     |     |     |      |     |     |     |      |     |     |     |      |     |     |     |     |     |
|--------|-----------------|---------------|------|-----|-----|-----|------|-----|-----|-----|------|-----|-----|-----|------|-----|-----|-----|-----|-----|
| 器具効率   | 75 %            | 天井            | 80 % |     |     |     | 70 % |     |     |     | 50 % |     |     |     | 30 % |     |     |     | 0 % |     |
|        |                 | 壁             | 70   | 50  | 30  | 10  | 70   | 50  | 30  | 10  | 70   | 50  | 30  | 10  | 70   | 50  | 30  | 10  | 0 % |     |
|        |                 | 床             | 10 % |     |     |     | 10 % |     |     |     | 10 % |     |     |     | 10 % |     |     |     | 0 % |     |
| 上方光束   | 1 %             | 室指数           |      |     |     |     |      |     |     |     |      |     |     |     |      |     |     |     |     |     |
| 下方光束   | 74 %            | 照明率 ( X0.01 ) |      |     |     |     |      |     |     |     |      |     |     |     |      |     |     |     |     |     |
|        |                 | ZCM           |      |     |     |     |      |     |     |     |      |     |     |     |      |     |     |     |     |     |
| 保守率    | 良               | 0.67          | 0.6  | 4.6 | 3.8 | 3.2 | 2.9  | 4.5 | 3.7 | 3.2 | 2.9  | 4.3 | 3.6 | 3.2 | 2.9  | 4.2 | 3.6 | 3.1 | 2.8 | 2.7 |
|        | 中               | 0.63          | 0.8  | 5.4 | 4.7 | 4.1 | 3.8  | 5.3 | 4.6 | 4.1 | 3.8  | 5.1 | 4.5 | 4.1 | 3.7  | 4.9 | 4.4 | 4.0 | 3.7 | 3.5 |
|        | 否               | 0.56          | 1.0  | 5.9 | 5.2 | 4.7 | 4.4  | 5.8 | 5.2 | 4.7 | 4.3  | 5.6 | 5.0 | 4.6 | 4.3  | 5.4 | 4.9 | 4.6 | 4.3 | 4.1 |
|        |                 |               | 1.25 | 6.3 | 5.7 | 5.3 | 4.9  | 6.2 | 5.6 | 5.2 | 4.9  | 6.0 | 5.5 | 5.1 | 4.8  | 5.8 | 5.4 | 5.0 | 4.8 | 4.6 |
| 下方投影面積 | cm <sup>2</sup> |               | 1.5  | 6.6 | 6.0 | 5.6 | 5.3  | 6.5 | 6.0 | 5.6 | 5.3  | 6.2 | 5.8 | 5.5 | 5.2  | 6.0 | 5.7 | 5.4 | 5.1 | 5.0 |
| 等価発光面積 | cm <sup>2</sup> |               | 2.0  | 7.0 | 6.5 | 6.1 | 5.8  | 6.8 | 6.4 | 6.1 | 5.8  | 6.6 | 6.3 | 6.0 | 5.7  | 6.4 | 6.1 | 5.9 | 5.6 | 5.4 |
| 取付高さ   | 器具間隔最大限         |               | 2.5  | 7.2 | 6.8 | 6.5 | 6.2  | 7.1 | 6.7 | 6.4 | 6.2  | 6.8 | 6.5 | 6.3 | 6.1  | 6.6 | 6.4 | 6.2 | 6.0 | 5.8 |
|        | 横方向 (A)         | 縦方向 (B)       | 3.0  | 7.3 | 7.0 | 6.7 | 6.5  | 7.2 | 6.9 | 6.6 | 6.4  | 7.0 | 6.7 | 6.5 | 6.3  | 6.8 | 6.6 | 6.4 | 6.2 | 6.0 |
| Hm     | 1.36Hm          | 1.36Hm        | 4.0  | 7.5 | 7.3 | 7.0 | 6.8  | 7.4 | 7.2 | 6.9 | 6.8  | 7.2 | 7.0 | 6.8 | 6.6  | 7.0 | 6.8 | 6.7 | 6.5 | 6.3 |
|        |                 |               | 5.0  | 7.6 | 7.4 | 7.2 | 7.0  | 7.5 | 7.3 | 7.1 | 7.0  | 7.3 | 7.1 | 7.0 | 6.8  | 7.1 | 7.0 | 6.8 | 6.7 | 6.5 |
|        |                 |               | 7.0  | 7.8 | 7.6 | 7.5 | 7.3  | 7.6 | 7.5 | 7.4 | 7.2  | 7.4 | 7.3 | 7.2 | 7.1  | 7.2 | 7.1 | 7.0 | 7.0 | 6.7 |
|        |                 |               | 10.0 | 7.9 | 7.7 | 7.6 | 7.5  | 7.7 | 7.6 | 7.5 | 7.5  | 7.5 | 7.5 | 7.4 | 7.3  | 7.3 | 7.3 | 7.2 | 7.1 | 6.9 |

