

屋内照明器具特性	
品番 (品名)	LSEW4000WU
光源	LDA4L-H-E17/E/S/W/2 ×1 440.0 1m
管理番号	K0123403(1)DB1
BZ分類	BZ9/3.5/BZ8

器具効率	57%	反射率	天井	80%				70%				50%				30%				0%
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
上方光束	24%	床	10%				10%				10%				10%				0%	
下方光束	33%	室指数	照明率 (X0.01)																ZCM	
保守率	良 0.63	0.6	2.5	1.8	1.3	1.0	2.3	1.6	1.2	0.9	1.9	1.4	1.0	0.8	1.6	1.1	0.8	0.6	0.4	
	中 0.6	0.8	3.0	2.3	1.8	1.4	2.7	2.1	1.6	1.3	2.3	1.8	1.4	1.1	1.9	1.5	1.2	0.9	0.6	
	否 0.56	1.0	3.3	2.6	2.1	1.7	3.1	2.4	2.0	1.6	2.6	2.1	1.7	1.4	2.1	1.7	1.4	1.2	0.8	
		1.25	3.6	3.0	2.5	2.1	3.4	2.8	2.3	2.0	2.8	2.4	2.0	1.7	2.3	2.0	1.7	1.4	1.0	
下方投影面積	cm ²	1.5	3.9	3.3	2.8	2.4	3.6	3.0	2.6	2.2	3.0	2.6	2.2	1.9	2.5	2.2	1.9	1.6	1.1	
等価発光面積		2.0	4.2	3.7	3.2	2.9	3.9	3.4	3.0	2.7	3.3	2.9	2.6	2.3	2.7	2.4	2.2	2.0	1.4	
取付高さ	器具間隔最大限		2.5	4.4	3.9	3.5	3.2	4.1	3.7	3.3	3.0	3.5	3.1	2.9	2.6	2.9	2.7	2.4	2.2	1.6
	横方向 (A)	縦方向 (B)	3.0	4.6	4.2	3.8	3.5	4.3	3.9	3.5	3.2	3.6	3.3	3.1	2.8	3.1	2.8	2.6	2.4	1.7
Hm	1.59Hm	2.31Hm	4.0	4.8	4.4	4.1	3.8	4.5	4.1	3.8	3.6	3.8	3.6	3.3	3.1	3.2	3.0	2.8	2.7	2.0
			5.0	4.9	4.6	4.3	4.1	4.6	4.3	4.1	3.8	4.0	3.7	3.5	3.3	3.4	3.2	3.0	2.9	2.1
			7.0	5.1	4.8	4.6	4.4	4.8	4.5	4.3	4.1	4.1	3.9	3.8	3.6	3.5	3.4	3.2	3.1	2.4
			10.0	5.2	5.0	4.9	4.7	4.9	4.7	4.6	4.4	4.3	4.1	4.0	3.9	3.6	3.5	3.4	3.3	2.5

