

屋内照明器具特性	
品番 (品名)	LSEW4001YZ
光源	LDA4L-H-E17/E/S/W/2 ×1 440.0 1m
管理番号	K0160307(0)DR1
BZ分類	BZ9

器具効率	50%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	25%	床	10%				10%				10%				10%				0%	
下方光束	25%	室指数	照明率 (X0.01)																ZCM	
保守率	良 0.63	0.6	2.2	1.6	1.2	0.9	2.0	1.4	1.1	0.8	1.6	1.2	0.9	0.7	1.3	0.9	0.7	0.5	0.3	
	中 0.6	0.8	2.6	2.0	1.5	1.2	2.4	1.8	1.4	1.1	1.9	1.5	1.2	1.0	1.5	1.2	1.0	0.8	0.4	
	否 0.56	1.0	2.9	2.3	1.9	1.5	2.6	2.1	1.7	1.4	2.1	1.7	1.4	1.2	1.7	1.4	1.1	1.0	0.6	
		1.25	3.2	2.6	2.2	1.8	2.9	2.4	2.0	1.7	2.4	2.0	1.7	1.4	1.9	1.6	1.4	1.2	0.7	
下方投影面積	cm ²	1.5	3.4	2.8	2.4	2.1	3.1	2.6	2.2	1.9	2.5	2.2	1.9	1.6	2.0	1.7	1.5	1.3	0.8	
		2.0	3.6	3.2	2.8	2.5	3.3	2.9	2.6	2.3	2.8	2.4	2.2	1.9	2.2	2.0	1.8	1.6	1.0	
取付高さ	器具間隔最大限		2.5	3.8	3.4	3.1	2.8	3.5	3.1	2.8	2.6	2.9	2.6	2.4	2.2	2.4	2.1	2.0	1.8	1.2
	横方向 (A)	縦方向 (B)	3.0	4.0	3.6	3.3	3.0	3.6	3.3	3.0	2.8	3.0	2.8	2.6	2.4	2.5	2.3	2.1	1.9	1.3
Hm	1.65Hm	1.55Hm	4.0	4.1	3.8	3.6	3.3	3.8	3.5	3.3	3.1	3.2	3.0	2.8	2.6	2.6	2.4	2.3	2.2	1.5
			5.0	4.2	4.0	3.7	3.5	3.9	3.7	3.5	3.3	3.3	3.1	2.9	2.8	2.7	2.6	2.4	2.3	1.6
			7.0	4.4	4.2	4.0	3.8	4.1	3.9	3.7	3.5	3.4	3.3	3.1	3.0	2.8	2.7	2.6	2.5	1.8
			10.0	4.5	4.3	4.2	4.0	4.2	4.0	3.9	3.8	3.5	3.4	3.3	3.2	2.9	2.9	2.8	2.7	1.9

