

屋内照明器具特性

品番 (品名)	LSEB3124									
光源	LED2700_70_192 x1					192.0 l m				
管理番号	K0150112(0)DB1									
BZ分類	BZ1/0.7/BZ2/2.3/BZ3									

器具効率	100%	天井	80%				70%				50%				30%				0%	
	上方光束 3%		反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
				下方光束 97%	10%				10%				10%				10%			
室指数	照明率 (X0.01)																			ZCM
保守率	良	0.67	0.6	71	62	56	52	70	61	56	52	67	60	55	52	65	59	55	51	50
	中	0.63	0.8	78	70	64	60	77	69	63	60	74	67	63	59	72	66	62	59	57
	否	0.56	1.0	83	75	69	65	81	74	69	65	79	73	68	64	76	71	67	64	62
			1.25	87	80	75	71	86	79	74	70	83	77	73	69	80	75	72	69	66
下方投影面積			1.5	90	84	79	75	88	83	78	74	86	81	77	73	83	79	75	72	70
	等価発光面積		2.0	94	89	84	81	92	87	83	80	89	85	82	79	87	83	80	78	75
取付高さ	器具間隔最大限		2.5	96	92	88	85	95	91	87	84	92	88	85	82	89	86	83	81	78
	横方向 (A)	縦方向 (B)	3.0	98	94	91	88	97	93	90	87	93	90	88	85	91	88	86	84	81
Hm	1.18Hm	1.18Hm	4.0	100	97	94	92	99	96	93	91	96	93	91	89	93	91	89	87	84
			5.0	102	99	97	94	100	98	95	93	97	95	93	91	94	92	91	89	86
			7.0	103	101	99	98	102	100	98	96	99	97	96	94	96	94	93	92	89
			10.0	104	103	102	100	103	102	100	99	100	99	98	97	97	96	95	94	91

