

屋内照明器具特性

品番 (品名)	NTS62812S+NTS90201	
光源	LED3500_70_835 x1	835.0 1m
管理番号	K0156488(1)DJ1	
BZ分類	BZ1	

器具効率	102%	天井	80%				70%				50%				30%				0%		
			70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10			
上方光束	0%	反射率	壁	70				70				70				70				0%	
下方光束	102%		床	10%				10%				10%				10%				0%	
室指数		照明率 (X0.01)																			ZCM
保守率	良 0.67	0.6	1.02	1.00	0.98	0.97	1.02	1.00	0.98	0.97	1.01	0.99	0.98	0.97	1.01	0.99	0.98	0.97	0.96		
	中 0.63	0.8	1.04	1.02	1.00	0.99	1.04	1.01	1.00	0.99	1.03	1.01	1.00	0.99	1.02	1.00	0.99	0.98	0.98		
	否 0.56	1.0	1.05	1.03	1.02	1.00	1.05	1.03	1.01	1.00	1.03	1.02	1.01	1.00	1.03	1.01	1.00	0.99	0.99		
下方投影面積	cm ²	1.25	1.06	1.04	1.03	1.02	1.05	1.04	1.02	1.01	1.04	1.03	1.02	1.01	1.03	1.02	1.01	1.00	0.99		
		1.5	1.07	1.05	1.04	1.03	1.06	1.04	1.03	1.02	1.05	1.03	1.02	1.01	1.03	1.02	1.01	1.00	1.00		
等価発光面積	cm ²	2.0	1.08	1.06	1.05	1.04	1.07	1.05	1.04	1.03	1.05	1.04	1.03	1.03	1.04	1.03	1.02	1.01	1.00		
		2.5	1.08	1.07	1.06	1.05	1.07	1.06	1.05	1.04	1.06	1.05	1.04	1.03	1.04	1.03	1.03	1.02	1.01		
取付高さ	器具間隔最大限		3.0	1.09	1.07	1.06	1.06	1.08	1.07	1.06	1.05	1.06	1.05	1.04	1.04	1.04	1.03	1.03	1.01		
	Hm	0.25Hm		0.25Hm	4.0	1.09	1.08	1.07	1.07	1.08	1.07	1.07	1.06	1.06	1.05	1.05	1.04	1.04	1.03	1.01	
Hm	0.25Hm	0.25Hm	5.0	1.09	1.09	1.08	1.07	1.08	1.08	1.07	1.07	1.06	1.06	1.05	1.05	1.05	1.04	1.04	1.03	1.01	
			7.0	1.10	1.09	1.09	1.08	1.09	1.08	1.08	1.07	1.07	1.06	1.06	1.06	1.05	1.04	1.04	1.04	1.01	
			10.0	1.10	1.10	1.09	1.09	1.09	1.09	1.08	1.08	1.07	1.07	1.06	1.06	1.05	1.05	1.04	1.01		

