

屋内照明器具特性

品番 (品名)	NTS71242S+NTS90101	
光源	LED3500_85_720 x1	720.0 lm
管理番号	K0161313(0)DB1	
BZ分類	BZ4	

器具効率	100%	天井	80%				70%				50%				30%				0%		
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%		
上方光束	1%	床	10%				10%				10%				10%				0%		
下方光束	99%	室指数	照明率 (X0.01)																ZCM		
保守率	良 中 否	0.81	0.6	5.9	4.7	4.0	3.4	5.8	4.7	3.9	3.4	5.5	4.5	3.9	3.4	5.3	4.4	3.8	3.4	3.2	
		0.77	0.8	7.0	5.9	5.1	4.6	6.8	5.8	5.1	4.6	6.5	5.7	5.0	4.6	6.3	5.5	5.0	4.5	4.3	
		0.68	1.0	7.6	6.7	6.0	5.4	7.5	6.6	5.9	5.4	7.2	6.4	5.8	5.4	6.9	6.3	5.7	5.3	5.1	
			1.25	8.2	7.4	6.7	6.2	8.1	7.3	6.6	6.2	7.8	7.1	6.5	6.1	7.5	6.9	6.4	6.0	5.8	
下方投影面積		c m ²		1.5	8.6	7.8	7.2	6.7	8.5	7.7	7.2	6.7	8.2	7.5	7.0	6.6	7.9	7.4	6.9	6.6	6.3
等価発光面積		c m ²		2.0	9.1	8.5	8.0	7.5	9.0	8.4	7.9	7.5	8.7	8.2	7.7	7.4	8.4	8.0	7.6	7.3	7.0
取付高さ	器具間隔最大限		2.5	9.5	8.9	8.4	8.0	9.3	8.8	8.4	8.0	9.0	8.6	8.2	7.9	8.7	8.4	8.1	7.8	7.5	
	横方向 (A)	縦方向 (B)	3.0	9.7	9.2	8.8	8.4	9.5	9.1	8.7	8.3	9.2	8.9	8.5	8.2	9.0	8.6	8.4	8.1	7.8	
H _m	0.91H _m	1.22H _m	4.0	10.0	9.6	9.2	8.9	9.8	9.4	9.1	8.8	9.5	9.2	9.0	8.7	9.3	9.0	8.8	8.6	8.3	
			5.0	10.1	9.8	9.5	9.2	10.0	9.7	9.4	9.2	9.7	9.4	9.2	9.0	9.4	9.2	9.0	8.9	8.6	
			7.0	10.3	10.1	9.8	9.6	10.2	9.9	9.7	9.6	9.9	9.7	9.5	9.4	9.6	9.5	9.3	9.2	8.9	
			10.0	10.5	10.3	10.1	10.0	10.3	10.2	10.0	9.9	10.1	9.9	9.8	9.7	9.8	9.7	9.6	9.5	9.2	

