

屋内照明器具特性

品番 (品名)	XND2051PL														
光源	LED3000_85_1335 x1 1335.0lm														
管理番号	K0163222(0)DB1														
BZ分類	BZ4														

器具効率	100%	天井	80%				70%				50%				30%				0%		
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
				床	10%				10%				10%				10%				0%
上方光束 下方光束	0% 100%	室指数	照明率 (X0.01) ZCM																		
保守率	良 中 否 0.83 0.81 0.77	0.6	58	47	39	34	57	46	39	34	55	45	38	34	53	44	38	34	32		
		0.8	69	58	50	45	67	57	50	44	65	56	49	44	62	54	48	44	42		
		1.0	75	65	58	52	74	64	57	52	71	63	57	52	68	61	56	51	49		
		1.25	81	72	65	60	80	71	65	59	77	69	64	59	74	68	63	59	56		
下方投影面積 等価発光面積	c m ² c m ²	1.5	85	77	70	65	84	76	70	65	81	74	69	64	78	72	68	64	61		
		2.0	91	84	78	73	89	83	77	73	86	81	76	72	83	79	75	71	69		
取付 高さ	器具間隔最大限		2.5	94	88	83	79	92	87	82	78	89	85	81	77	87	83	79	76	74	
	横方向 (A) 縦方向 (B)	3.0	96	91	87	83	95	90	86	82	92	88	84	81	89	86	83	80	78		
H m	1.21H m	1.21H m	4.0	99	95	92	88	98	94	91	88	95	92	89	86	92	90	87	85	82	
			5.0	101	98	95	92	100	96	94	91	97	94	92	90	94	92	90	88	86	
			7.0	103	101	98	96	102	99	97	95	99	97	95	94	97	95	93	92	89	
			10.0	105	103	101	99	103	102	100	99	101	99	98	97	98	97	96	95	92	

