

屋内照明器具特性	
品番 (品名)	L G W C 8 5 0 2 1 B F
光源	LDA4L - H - E17 / E / S / W / 2 ×1 440.0 1 m
管理番号	K0122872 ( 1 ) DB 1
B Z 分類	BZ10

器具効率	39 %	天井	80 %				70 %				50 %				30 %				0 %
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
上方光束	21 %	床	10 %				10 %				10 %				10 %				0 %
下方光束	18 %	室指数	照明率 ( X0.01 )																ZCM
保守率	良 中 否 0.63 0.6 0.56	0.6	17	12	8	6	15	10	8	6	12	8	6	4	9	6	5	3	1
		0.8	20	15	11	9	18	13	10	8	14	11	8	7	11	8	6	5	2
		1.0	22	17	14	11	20	16	13	10	16	13	10	8	12	10	8	6	3
		1.25	24	20	16	14	22	18	15	12	18	15	12	10	14	11	9	8	4
下方投影面積	c m <sup>2</sup>	1.5	26	22	18	16	23	20	17	14	19	16	14	12	15	13	11	9	5
		2.0	28	24	21	19	26	22	19	17	21	18	16	14	16	14	13	11	6
取付高さ	器具間隔最大限		2.5	30	26	23	21	27	24	21	19	22	20	18	16	17	16	14	8
	横方向 ( A )	縦方向 ( B )	3.0	31	28	25	23	28	25	23	21	23	21	19	17	18	17	15	9
H m	0.00 H m	2.18 H m	4.0	32	30	27	25	29	27	25	23	24	22	21	19	19	18	17	10
			5.0	33	31	29	27	30	28	27	25	25	24	22	21	20	19	18	17
			7.0	34	32	31	29	31	30	28	27	26	25	24	23	21	20	19	12
			10.0	35	34	32	31	32	31	30	29	27	26	25	24	22	21	20	14

