

屋内照明器具特性

品番 (品名)	LGWJ 85110U														
光源	LDA4L-H-E17/E/S/W/2 ×1 440.0 1m														
管理番号	K0125722(1)DB1														
BZ分類	BZ5														

器具効率	42 %	天井	80 %				70 %				50 %				30 %				0 %	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
		床	10 %				10 %				10 %				10 %				0 %	
上方光束	5 %	室指数																		
下方光束	37 %	照明率 (X0.01)																		
		ZCM																		
保守率	良 中 否	0.63	0.6	23	17	14	12	22	17	14	11	20	16	13	11	19	15	13	11	10
		0.6	0.8	27	22	18	16	26	21	18	15	24	20	17	15	22	19	16	14	13
		0.56	1.0	29	25	21	19	28	24	21	18	26	23	20	18	24	21	19	17	16
			1.25	32	27	24	22	31	27	24	21	28	25	23	21	27	24	22	20	18
下方投影面積		cm ²																		
等価発光面積		cm ²																		
取付高さ	器具間隔最大限		2.5	37	34	32	30	36	34	31	29	34	32	30	28	32	30	28	27	25
	横方向 (A)	縦方向 (B)	3.0	38	36	34	32	37	35	33	31	35	33	31	30	33	31	30	28	26
H _m	1.24H _m	1.30H _m	4.0	40	38	36	34	39	37	35	34	36	35	33	32	34	33	32	31	28
			5.0	41	39	37	36	39	38	36	35	37	36	35	34	35	34	33	32	30
			7.0	42	40	39	38	40	39	38	37	38	37	36	35	36	35	34	34	31
			10.0	42	41	41	40	41	40	40	39	39	38	38	37	37	36	36	35	32

