

屋内照明器具特性

品番 (品名)	LGW51717Y														
光源	LLD4300N ×1 930.0 lm														
管理番号	K0166016(0)DB1														
BZ分類	BZ5														

器具効率	72%	天井	80%				70%				50%				30%				0%			
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%			
		床	10%				10%				10%				10%				0%			
上方光束	0%	室指数																				
下方光束	72%	照明率 (×0.01)																				
		ZCM																				
保守率	良 中 否	0.63	0.6	0.56	0.6	41	32	27	23	40	32	27	23	38	31	26	23	37	30	26	23	21
		0.6	0.8	48	40	34	30	47	40	34	30	45	38	34	30	43	37	33	30	28		
		1.0	53	45	40	36	52	45	40	36	50	44	39	35	48	42	38	35	33			
		0.56	1.25	57	50	45	41	56	50	45	41	54	48	44	41	52	47	43	40	38		
下方投影面積			cm ²		1.5	60	54	49	45	59	53	49	45	57	52	48	44	55	50	47	44	42
			cm ²		2.0	64	59	55	51	63	58	54	51	61	57	53	50	59	55	52	49	48
取付高さ	器具間隔最大限				2.5	67	62	58	55	66	61	58	55	63	60	57	54	61	58	56	53	51
	横方向 (A)	縦方向 (B)			3.0	69	65	61	58	67	64	61	58	65	62	59	57	63	60	58	56	54
Hm	1.26Hm	1.26Hm			4.0	71	68	65	62	70	67	64	62	68	65	63	61	66	63	62	60	58
				5.0	72	70	67	65	71	69	66	64	69	67	65	63	67	65	64	62	60	
				7.0	74	72	70	68	73	71	69	68	71	69	68	66	69	67	66	65	63	
				10.0	75	74	72	71	74	73	71	70	72	71	70	69	70	69	68	67	65	

