

屋内照明器具特性	
品番 (品名)	NNF W2 1 0 2 1 J
光源	LDL20S.N/11/12(960) ×1 960.0 1 m
管理番号	K0125167(3)DR1
BZ分類	BZ6/0.7/BZ5/3.5/BZ6/4.5/BZ5 /6.0/BZ6

器具効率	98%	天井	80%				70%				50%				30%				0%		
	上方光束		12%	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
	下方光束		86%		床	10%				10%				10%				10%			
室指数	照明率 (X0.01)																			ZCM	
保守率	良	0.83	0.6	5.2	4.0	3.2	2.6	5.0	3.9	3.1	2.6	4.6	3.7	3.0	2.5	4.3	3.5	2.9	2.5	2.2	
	中	0.81	0.8	6.1	4.9	4.1	3.6	5.9	4.8	4.1	3.5	5.5	4.5	3.9	3.4	5.1	4.3	3.7	3.3	3.0	
	否	0.77	1.0	6.7	5.6	4.8	4.2	6.5	5.5	4.7	4.2	6.0	5.2	4.5	4.0	5.6	4.9	4.3	3.9	3.5	
	下方投影面積		1.25	7.3	6.3	5.5	4.9	7.0	6.1	5.4	4.8	6.6	5.8	5.2	4.7	6.1	5.4	4.9	4.5	4.1	
等価発光面積		1.5	7.7	6.8	6.0	5.4	7.4	6.6	5.9	5.3	6.9	6.2	5.6	5.1	6.5	5.9	5.4	5.0	4.5		
		2.0	8.2	7.4	6.8	6.2	8.0	7.2	6.6	6.1	7.5	6.8	6.3	5.9	7.0	6.5	6.0	5.6	5.2		
取付高さ	器具間隔最大限		2.5	8.6	7.9	7.3	6.8	8.3	7.7	7.1	6.7	7.8	7.3	6.8	6.4	7.3	6.9	6.5	6.1	5.6	
	横方向 (A)	縦方向 (B)	3.0	8.8	8.2	7.7	7.2	8.6	8.0	7.5	7.1	8.0	7.6	7.1	6.8	7.5	7.2	6.8	6.5	6.0	
1.5m	2.06m	1.85m	4.0	9.2	8.7	8.2	7.8	8.9	8.4	8.0	7.6	8.4	8.0	7.6	7.3	7.9	7.6	7.3	7.0	6.5	
2	2.74	2.43	5.0	9.4	8.9	8.5	8.2	9.1	8.7	8.3	8.0	8.6	8.2	7.9	7.7	8.1	7.8	7.6	7.3	6.8	
2.5	3.42	3.01	7.0	9.6	9.3	9.0	8.7	9.3	9.0	8.8	8.5	8.8	8.6	8.3	8.1	8.3	8.1	7.9	7.8	7.2	
3	4.12	3.6	10.0	9.8	9.6	9.3	9.1	9.5	9.3	9.1	8.9	9.0	8.8	8.7	8.5	8.6	8.4	8.2	8.1	7.5	

