

# 屋内照明器具特性

品番 (品名)	NNF W2 2 0 2 0 J									
光源	LDL20S . N / 11 / 12 ( 9 6 0 ) × 2					9 6 0 . 0 1 m				
管理番号	K0125168 ( 3 ) DR 1									
B Z 分類	BZ6 / 0 . 7 / BZ5 / 0 . 9 / BZ6									

器具効率	97 %	天井	80 %				70 %				50 %				30 %				0 %		
	上方光束		13 %	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
	下方光束		84 %		床	10 %				10 %				10 %				10 %			
室指数	照明率 ( X 0 . 0 1 )																			Z C M	
保守率	良	0.83	0.6	51	39	31	26	49	38	30	25	45	36	29	25	42	34	28	24	21	
	中	0.81	0.8	60	48	40	35	58	47	40	34	54	44	38	33	50	42	36	32	29	
	否	0.77	1.0	66	55	47	41	64	53	46	40	59	50	44	39	55	48	42	38	34	
	下方投影面積	c m <sup>2</sup>		1.25	72	61	54	48	69	60	52	47	64	56	50	45	60	53	48	43	39
等価発光面積	c m <sup>2</sup>		1.5	76	66	59	53	73	64	57	52	68	61	55	50	63	57	52	48	44	
	c m <sup>2</sup>		2.0	81	73	66	61	78	71	65	59	73	67	62	57	68	63	59	55	50	
取付高さ	器具間隔最大限		2.5	85	77	71	66	82	75	70	65	76	71	66	62	71	67	63	60	55	
	横方向 ( A )	縦方向 ( B )	3.0	87	81	75	70	84	78	73	69	79	74	70	66	74	70	66	63	58	
1.5m	2.05 m	1.86 m	4.0	90	85	80	76	87	83	78	75	82	78	75	71	77	74	71	68	63	
2	2.72	2.44	5.0	92	88	84	80	90	86	82	78	84	81	78	75	79	77	74	72	66	
2.5	3.4	3.02	7.0	95	91	88	85	92	89	86	83	87	84	82	80	82	80	78	76	70	
3	4.09	3.6	10.0	97	94	92	89	94	92	89	87	89	87	85	83	84	82	81	79	73	

