

屋内照明器具特性	
品番 (品名)	NNF W2 1 2 5 1 J
光源	LDL20S . N / 11 / 12 (960) ×1 960.0 1 m
管理番号	K0125114 (0) DR 1
B Z 分類	BZ6 / 0.7 / BZ5

器具効率	98 %	天井	80 %				70 %				50 %				30 %				0 %	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
上方光束	3 %	床	10 %				10 %				10 %				10 %				0 %	
下方光束	95 %	室指数	照明率 (X0.01)																ZCM	
保守率	良	0.81	0.6	53	41	33	27	52	40	32	27	49	39	32	27	46	37	31	26	24
	中	0.77	0.8	63	51	43	37	61	50	42	36	58	48	41	36	55	46	40	36	33
	否	0.68	1.0	69	58	50	43	67	57	49	43	64	55	48	43	61	53	47	42	39
			1.25	75	64	57	50	73	63	56	50	69	61	55	49	66	59	53	49	46
下方投影面積		cm ²	1.5	79	69	62	56	77	68	61	55	73	66	59	54	70	63	58	54	51
等価発光面積		cm ²	2.0	84	76	69	64	82	75	69	63	79	72	67	62	75	70	65	61	58
取付高さ	器具間隔最大限		2.5	88	81	75	70	86	79	74	69	82	77	72	68	79	74	70	66	63
	横方向 (A)	縦方向 (B)	3.0	90	84	79	74	88	83	78	73	85	80	76	72	81	77	74	70	67
1.5m	2.06 m	1.88 m	4.0	94	89	84	80	92	87	83	79	88	84	81	77	85	82	78	76	72
2	2.74	2.46	5.0	96	91	87	84	94	90	86	83	90	87	84	81	87	84	82	79	76
2.5	3.42	3.05	7.0	98	95	92	89	96	93	90	88	93	90	88	86	90	88	86	84	80
3	4.11	3.65	10.0	100	98	95	93	98	96	94	92	95	93	91	90	92	90	89	87	84

