

# 屋内照明器具特性

|         |                              |  |
|---------|------------------------------|--|
| 品番 (品名) | XLX450RHVP                   |  |
| 光源      | LED3500_85_4590 x1 4590.0 lm |  |
| 管理番号    | K0137981(4)DB1               |  |
| BZ分類    | BZ5                          |  |

|        |                 |         |      |      |      |      |     |      |      |     |     |      |     |     |     |     |     |     |     |     |
|--------|-----------------|---------|------|------|------|------|-----|------|------|-----|-----|------|-----|-----|-----|-----|-----|-----|-----|-----|
| 器具効率   | 100%            | 天井      | 80%  |      |      |      | 70% |      |      |     | 50% |      |     |     | 30% |     |     |     | 0%  |     |
|        | 上方光束<br>0%      |         | 反射率  | 70   | 50   | 30   | 10  | 70   | 50   | 30  | 10  | 70   | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 0%  |
| 下方光束   | 100%            | 床       |      | 10%  |      |      |     | 10%  |      |     |     | 10%  |     |     |     | 10% |     |     |     | 0%  |
| 室指数    | 照明率 ( X0.01 )   |         |      |      |      |      |     |      |      |     |     |      |     |     |     |     |     |     |     | ZCM |
| 保守率    | 良               | 0.81    | 0.6  | 5.6  | 4.4  | 3.6  | 3.1 | 5.5  | 4.3  | 3.6 | 3.0 | 5.3  | 4.2 | 3.5 | 3.0 | 5.0 | 4.1 | 3.5 | 3.0 | 2.8 |
|        | 中               | 0.77    | 0.8  | 6.6  | 5.5  | 4.7  | 4.1 | 6.5  | 5.4  | 4.6 | 4.1 | 6.2  | 5.3 | 4.6 | 4.1 | 5.9 | 5.1 | 4.5 | 4.0 | 3.8 |
|        | 否               | 0.68    | 1.0  | 7.3  | 6.2  | 5.4  | 4.8 | 7.1  | 6.1  | 5.4 | 4.8 | 6.8  | 6.0 | 5.3 | 4.8 | 6.6 | 5.8 | 5.2 | 4.8 | 4.5 |
|        |                 |         | 1.25 | 7.9  | 6.9  | 6.2  | 5.6 | 7.7  | 6.8  | 6.1 | 5.6 | 7.4  | 6.6 | 6.0 | 5.5 | 7.1 | 6.5 | 5.9 | 5.5 | 5.3 |
| 下方投影面積 | cm <sup>2</sup> |         | 1.5  | 8.3  | 7.4  | 6.7  | 6.2 | 8.2  | 7.3  | 6.7 | 6.1 | 7.8  | 7.1 | 6.6 | 6.1 | 7.6 | 6.9 | 6.4 | 6.0 | 5.8 |
| 等価発光面積 | cm <sup>2</sup> |         | 2.0  | 8.9  | 8.2  | 7.5  | 7.0 | 8.7  | 8.0  | 7.5 | 7.0 | 8.4  | 7.8 | 7.3 | 6.9 | 8.1 | 7.6 | 7.2 | 6.8 | 6.6 |
| 取付高さ   | 器具間隔最大限         |         | 2.5  | 9.3  | 8.6  | 8.1  | 7.6 | 9.1  | 8.5  | 8.0 | 7.6 | 8.8  | 8.3 | 7.9 | 7.5 | 8.5 | 8.1 | 7.7 | 7.4 | 7.1 |
|        | 横方向 (A)         | 縦方向 (B) |      |      |      |      |     |      |      |     |     |      |     |     |     |     |     |     |     |     |
| 1.5m   | 2.01m           | 2.16m   | 4.0  | 9.8  | 9.4  | 9.0  | 8.7 | 9.7  | 9.3  | 8.9 | 8.6 | 9.4  | 9.1 | 8.7 | 8.5 | 9.1 | 8.8 | 8.6 | 8.3 | 8.1 |
| 2      | 2.65            | 2.71    | 5.0  | 10.0 | 9.7  | 9.3  | 9.0 | 9.9  | 9.6  | 9.2 | 9.0 | 9.6  | 9.3 | 9.1 | 8.8 | 9.3 | 9.1 | 8.9 | 8.7 | 8.4 |
| 2.5    | 3.29            | 3.29    | 7.0  | 10.3 | 10.0 | 9.7  | 9.5 | 10.1 | 9.9  | 9.6 | 9.4 | 9.8  | 9.6 | 9.4 | 9.3 | 9.6 | 9.4 | 9.3 | 9.1 | 8.8 |
| 3      | 3.93            | 3.89    | 10.0 | 10.4 | 10.2 | 10.1 | 9.9 | 10.3 | 10.1 | 9.9 | 9.8 | 10.0 | 9.9 | 9.7 | 9.6 | 9.8 | 9.7 | 9.5 | 9.4 | 9.1 |

