

# 屋内照明器具特性

|         |                    |           |
|---------|--------------------|-----------|
| 品番 (品名) | XLX451FHWP         |           |
| 光源      | LED4000_85_3250 x1 | 3250.0 lm |
| 管理番号    | K0132586(1)DB1     |           |
| BZ分類    | BZ2/8.5/BZ1        |           |

|        |                 |         |              |     |     |     |     |     |     |     |     |     |     |     |     |     |     |    |    |    |  |  |     |
|--------|-----------------|---------|--------------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|----|----|----|--|--|-----|
| 器具効率   | 100%            | 天井      | 80%          |     |     |     | 70% |     |     |     | 50% |     |     |     | 30% |     |     |    | 0% |    |  |  |     |
|        |                 | 壁       | 70           | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10 | 0% |    |  |  |     |
| 上方光束   | 0%              | 床       | 10%          |     |     |     | 10% |     |     |     | 10% |     |     |     | 10% |     |     |    | 0% |    |  |  |     |
| 下方光束   | 100%            | 室指数     | 照明率 ( X0.01) |     |     |     |     |     |     |     |     |     |     |     |     |     |     |    |    |    |  |  | ZCM |
| 保守率    | 良               | 0.81    | 0.6          | 66  | 56  | 50  | 46  | 65  | 56  | 50  | 45  | 63  | 55  | 49  | 45  | 61  | 54  | 49 | 45 | 44 |  |  |     |
|        | 中               | 0.77    | 0.8          | 77  | 69  | 63  | 59  | 76  | 68  | 63  | 58  | 74  | 67  | 62  | 58  | 72  | 66  | 61 | 58 | 56 |  |  |     |
|        | 否               | 0.68    | 1.0          | 84  | 77  | 71  | 67  | 83  | 76  | 71  | 67  | 81  | 75  | 70  | 67  | 79  | 73  | 69 | 66 | 65 |  |  |     |
|        |                 |         | 1.25         | 89  | 83  | 78  | 74  | 88  | 82  | 77  | 74  | 86  | 81  | 77  | 73  | 84  | 79  | 76 | 73 | 71 |  |  |     |
| 下方投影面積 | cm <sup>2</sup> |         | 1.5          | 93  | 87  | 82  | 79  | 91  | 86  | 82  | 78  | 89  | 84  | 81  | 78  | 87  | 83  | 80 | 77 | 75 |  |  |     |
|        | 等価発光面積          |         | 2.0          | 97  | 92  | 88  | 85  | 95  | 91  | 88  | 85  | 93  | 89  | 86  | 84  | 91  | 88  | 85 | 83 | 81 |  |  |     |
| 取付高さ   | 器具間隔最大限         |         | 2.5          | 99  | 95  | 92  | 89  | 98  | 94  | 91  | 89  | 95  | 93  | 90  | 88  | 93  | 91  | 89 | 87 | 85 |  |  |     |
|        | 横方向 (A)         | 縦方向 (B) | 3.0          | 101 | 97  | 94  | 92  | 99  | 96  | 94  | 91  | 97  | 95  | 92  | 90  | 95  | 93  | 91 | 89 | 87 |  |  |     |
| 1.5m   | 2.11m           | 2.1m    | 4.0          | 103 | 100 | 98  | 96  | 101 | 99  | 97  | 95  | 99  | 97  | 95  | 94  | 97  | 95  | 94 | 92 | 90 |  |  |     |
| 2      | 2.8             | 2.65    | 5.0          | 104 | 102 | 100 | 98  | 103 | 101 | 99  | 97  | 100 | 99  | 97  | 96  | 98  | 97  | 95 | 94 | 92 |  |  |     |
| 2.5    | 3.5             | 3.23    | 7.0          | 105 | 104 | 102 | 101 | 104 | 102 | 101 | 100 | 102 | 100 | 99  | 98  | 99  | 98  | 97 | 97 | 94 |  |  |     |
| 3      | 4.18            | 3.81    | 10.0         | 106 | 105 | 104 | 103 | 105 | 104 | 103 | 102 | 103 | 102 | 101 | 100 | 100 | 100 | 99 | 98 | 96 |  |  |     |

