

屋内照明器具特性

| | | | | | | | | | | |
|---------|------------------------------|--|--|--|--|--|--|--|--|--|
| 品番 (品名) | XLX454FENT | | | | | | | | | |
| 光源 | LED5000_85_3250 x1 3250.0 1m | | | | | | | | | |
| 管理番号 | K0132395(1)DB1 | | | | | | | | | |
| BZ分類 | BZ2 | | | | | | | | | |

| 器具効率 | 100% | 天井 | 80% | | | | 70% | | | | 50% | | | | 30% | | | | 0% | | | |
|--------|---------|---------|---------|------------------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|----|----|----|----|----|--|
| | | | 壁 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 0% | | |
| 上方光束 | 0% | 反射率 | 床 | 10% | | | | 10% | | | | 10% | | | | 10% | | | | 0% | | |
| 下方光束 | 100% | | 室指数 | 照明率 (X0.01) ZCM | | | | | | | | | | | | | | | | | | |
| 保守率 | 良 | 0.81 | 0.6 | 67 | 58 | 51 | 47 | 66 | 57 | 51 | 47 | 64 | 56 | 51 | 47 | 63 | 55 | 50 | 47 | 45 | | |
| | 中 | 0.77 | 0.8 | 77 | 68 | 63 | 58 | 76 | 68 | 62 | 58 | 74 | 67 | 62 | 58 | 72 | 66 | 61 | 58 | 56 | | |
| | 否 | 0.68 | 1.0 | 83 | 76 | 70 | 66 | 82 | 75 | 70 | 66 | 80 | 74 | 69 | 65 | 78 | 72 | 68 | 65 | 63 | | |
| | | | 1.25 | 88 | 81 | 76 | 72 | 87 | 81 | 76 | 72 | 85 | 79 | 75 | 72 | 82 | 78 | 74 | 71 | 69 | | |
| 下方投影面積 | | | 1.5 | 92 | 85 | 81 | 77 | 90 | 85 | 80 | 77 | 88 | 83 | 79 | 76 | 86 | 82 | 78 | 75 | 73 | | |
| | 等価発光面積 | | 2.0 | 96 | 91 | 87 | 83 | 94 | 90 | 86 | 83 | 92 | 88 | 85 | 82 | 90 | 86 | 84 | 81 | 79 | | |
| 取付高さ | 器具間隔最大限 | | 2.5 | 98 | 94 | 91 | 88 | 97 | 93 | 90 | 87 | 94 | 91 | 88 | 86 | 92 | 90 | 87 | 85 | 83 | | |
| | | 横方向 (A) | 縦方向 (B) | 3.0 | 100 | 96 | 93 | 91 | 99 | 95 | 92 | 90 | 96 | 93 | 91 | 89 | 94 | 92 | 90 | 88 | 85 | |
| 1.5m | 1.79m | 1.9m | 4.0 | 102 | 99 | 97 | 94 | 101 | 98 | 96 | 94 | 98 | 96 | 94 | 92 | 96 | 94 | 93 | 91 | 89 | | |
| 2 | 2.36 | 2.35 | 5.0 | 103 | 101 | 99 | 97 | 102 | 100 | 98 | 96 | 100 | 98 | 96 | 95 | 97 | 96 | 95 | 93 | 91 | | |
| 2.5 | 2.94 | 2.83 | 7.0 | 105 | 103 | 101 | 100 | 103 | 102 | 100 | 99 | 101 | 100 | 99 | 97 | 99 | 98 | 97 | 96 | 93 | | |
| 3 | 3.52 | 3.31 | 10.0 | 106 | 104 | 103 | 102 | 104 | 103 | 102 | 101 | 102 | 101 | 100 | 99 | 100 | 99 | 98 | 98 | 95 | | |

