

屋内照明器具特性	
品番 (品名)	XAS1014L
光源	LED2700_70_475 x1 475.0 lm
管理番号	K0170999(0)D 1
BZ分類	BZ4/8.5/BZ5

器具効率	100%	天井	80%				70%				50%				30%				0%		
	上方光束		11%	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
	下方光束		89%		床	10%				10%				10%				10%			
室指数	照明率 ( X0.01 )																			ZCM	
保守率	良	0.67	0.6	58	47	39	34	56	46	39	34	53	44	38	33	50	42	36	32	30	
	中	0.63	0.8	68	57	50	45	66	56	49	44	62	54	48	43	59	52	46	42	39	
	否	0.56	1.0	74	65	58	52	72	63	57	52	68	61	55	51	64	58	53	49	46	
			1.25	80	71	65	60	78	70	64	59	73	67	61	57	69	64	59	56	52	
下方投影面積			1.5	84	76	70	65	81	74	69	64	77	71	66	62	73	68	64	60	56	
			2.0	89	82	77	72	86	80	75	71	82	77	73	69	77	73	70	67	62	
取付高さ	器具間隔最大限		2.5	92	86	82	77	90	84	80	76	85	81	77	74	80	77	74	71	67	
	横方向 (A)	縦方向 (B)	3.0	94	89	85	81	92	87	83	80	87	83	80	77	82	79	77	74	69	
Hm	1.25Hm	1.25Hm	4.0	97	93	89	86	94	91	87	85	90	87	84	81	85	83	80	78	73	
			5.0	99	95	92	89	96	93	90	88	91	89	86	84	87	85	83	81	76	
			7.0	100	98	96	93	98	96	94	92	93	91	90	88	89	87	86	84	79	
			10.0	102	100	98	97	100	98	96	95	95	93	92	91	90	89	88	87	81	

