

屋内照明器具特性

品番 (品名)	XL573PHVK									
光源	LED5000_85_4790 x1 4790.0 1 m									
管理番号	K0162374 (1) DB 1									
BZ分類	BZ4									

器具効率	99 %	天井	80 %				70 %				50 %				30 %				0 %	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
		床	10 %				10 %				10 %				10 %				0 %	
上方光束	0 %																			
下方光束	99 %																			
室指数	照明率 (X0.01)																ZCM			
保守率	良 中 否	0.81	0.6	5.9	4.7	3.9	3.4	5.7	4.6	3.9	3.4	5.5	4.5	3.9	3.4	5.3	4.4	3.8	3.4	3.2
		0.77	0.8	6.9	5.8	5.0	4.5	6.7	5.7	5.0	4.5	6.5	5.6	4.9	4.5	6.2	5.5	4.9	4.4	4.2
		0.68	1.0	7.5	6.5	5.8	5.3	7.4	6.5	5.8	5.3	7.1	6.3	5.7	5.2	6.9	6.2	5.6	5.2	5.0
			1.25	8.1	7.2	6.6	6.0	8.0	7.1	6.5	6.0	7.7	7.0	6.4	6.0	7.4	6.8	6.3	5.9	5.7
下方投影面積		cm ²																		
等価発光面積		cm ²																		
取付高さ	器具間隔最大限		2.5	9.4	8.8	8.4	7.9	9.2	8.7	8.3	7.9	9.0	8.5	8.1	7.8	8.7	8.3	8.0	7.7	7.5
	横方向 (A)	縦方向 (B)																		
1.5m	1.84 m	1.84 m	4.0	9.9	9.5	9.2	8.9	9.8	9.4	9.1	8.8	9.5	9.2	8.9	8.7	9.2	9.0	8.8	8.6	8.3
2	2.43	2.43	5.0	10.1	9.8	9.5	9.2	9.9	9.7	9.4	9.1	9.7	9.4	9.2	9.0	9.4	9.2	9.0	8.9	8.6
2.5	2.96	2.96	7.0	10.3	10.1	9.8	9.6	10.2	9.9	9.7	9.5	9.9	9.7	9.5	9.4	9.7	9.5	9.4	9.2	9.0
3	3.55	3.56	10.0	10.4	10.3	10.1	10.0	10.3	10.1	10.0	9.9	10.1	9.9	9.8	9.7	9.8	9.7	9.6	9.5	9.2

