

屋内照明器具特性

品番 (品名)	XLGB82801	
光源	LED3500_70_400 ×1	400.0 lm
管理番号	K0171431(0)DB1	
BZ分類	BZ9/0.7/BZ8	

器具効率	100%	天井	80%				70%				50%				30%				0%		
	上方光束		44%	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
	下方光束		56%		床	10%				10%				10%				10%			
室指数	照明率 (X0.01)																			ZCM	
保守率	良	0.63	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	
	中	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	
	否	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	
	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	
下方投影面積	c m ²		1.25	65	54	46	39	60	50	43	37	51	43	37	32	42	36	31	27	18	
	等価発光面積	c m ²		1.5	69	59	51	44	64	55	47	42	54	47	41	36	45	39	34	30	21
取付高さ		器具間隔最大限		2.5	79	71	64	58	73	66	60	54	62	56	52	47	52	47	44	40	29
	H m	横方向 (A)	縦方向 (B)	3.0	81	74	68	63	76	69	64	59	64	59	55	51	54	50	47	43	32
1.61H m		1.66H m	4.0	85	79	74	69	79	74	69	65	68	64	60	56	57	54	51	48	35	
			5.0	87	82	77	73	81	77	72	69	70	66	63	60	59	56	54	51	38	
			7.0	90	86	82	79	84	80	77	74	73	70	67	64	62	59	57	55	42	
			10.0	92	89	86	83	86	83	81	78	75	73	70	68	64	62	60	59	45	

