

| | |
|----------|----------------------------|
| 屋内照明器具特性 | |
| 品番 (品名) | XLGB82916 |
| 光源 | LED3500_70_190 x1 190.0 lm |
| 管理番号 | K0169181(1)DR1 |
| BZ分類 | BZ5/0.7/BZ4 |

| | | | | | | | | | | | | | | | | | | | | |
|--------|---------|-----------------|--------------|----|----|----|-----|----|----|----|-----|----|----|----|-----|----|----|----|-----|----|
| 器具効率 | 100% | 天井 | 80% | | | | 70% | | | | 50% | | | | 30% | | | | 0% | |
| | | 壁 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 0% | |
| 上方光束 | 50% | 床 | 10% | | | | 10% | | | | 10% | | | | 10% | | | | 0% | |
| 下方光束 | 50% | 室指数 | 照明率 (X0.01) | | | | | | | | | | | | | | | | ZCM | |
| 保守率 | 良 | 0.63 | 0.6 | 51 | 40 | 32 | 27 | 47 | 37 | 31 | 26 | 40 | 32 | 27 | 23 | 33 | 27 | 23 | 20 | 15 |
| | 中 | 0.6 | 0.8 | 60 | 50 | 42 | 37 | 56 | 46 | 40 | 35 | 47 | 40 | 35 | 32 | 40 | 35 | 31 | 28 | 21 |
| | 否 | 0.56 | 1.0 | 66 | 57 | 50 | 45 | 61 | 53 | 47 | 42 | 52 | 46 | 41 | 38 | 44 | 39 | 36 | 33 | 25 |
| | | | 1.25 | 72 | 63 | 57 | 52 | 67 | 59 | 53 | 49 | 57 | 51 | 47 | 43 | 48 | 44 | 41 | 38 | 29 |
| 下方投影面積 | | cm ² | 1.5 | 76 | 68 | 62 | 57 | 70 | 64 | 58 | 54 | 60 | 55 | 51 | 48 | 51 | 47 | 44 | 41 | 32 |
| 等価発光面積 | | cm ² | 2.0 | 81 | 74 | 69 | 65 | 75 | 70 | 65 | 61 | 64 | 60 | 57 | 54 | 54 | 51 | 49 | 47 | 36 |
| 取付高さ | 器具間隔最大限 | | 2.5 | 84 | 79 | 74 | 70 | 78 | 73 | 69 | 66 | 67 | 63 | 60 | 58 | 57 | 54 | 52 | 50 | 38 |
| | 横方向 (A) | 縦方向 (B) | 3.0 | 86 | 81 | 77 | 74 | 80 | 76 | 72 | 69 | 69 | 66 | 63 | 61 | 58 | 56 | 54 | 52 | 40 |
| Hm | 0.00Hm | 1.64Hm | 4.0 | 89 | 85 | 82 | 79 | 83 | 80 | 77 | 74 | 71 | 69 | 67 | 65 | 60 | 58 | 57 | 56 | 42 |
| | | | 5.0 | 91 | 88 | 85 | 82 | 84 | 82 | 79 | 77 | 73 | 71 | 69 | 67 | 61 | 60 | 59 | 58 | 43 |
| | | | 7.0 | 93 | 90 | 88 | 86 | 86 | 84 | 82 | 81 | 74 | 73 | 71 | 70 | 63 | 62 | 61 | 60 | 45 |
| | | | 10.0 | 94 | 92 | 91 | 89 | 88 | 86 | 85 | 84 | 76 | 74 | 73 | 73 | 64 | 63 | 63 | 62 | 46 |

