

| 屋内照明器具特性 |                            |
|----------|----------------------------|
| 品番 (品名)  | XSLG104VS                  |
| 光源       | LED3500_70_140 x1 140.0 lm |
| 管理番号     | K0169176(0)DR1             |
| BZ分類     | BZ3                        |

|                  |                  |          |      |      |    |     |     |    |    |     |     |    |    |     |     |    |    |     |    |     |    |
|------------------|------------------|----------|------|------|----|-----|-----|----|----|-----|-----|----|----|-----|-----|----|----|-----|----|-----|----|
| 器具効率             | 100%             | 天井       | 80%  |      |    |     | 70% |    |    |     | 50% |    |    |     | 30% |    |    |     | 0% |     |    |
|                  | 上方光束             |          | 29%  | 壁    | 70 | 50  | 30  | 10 | 70 | 50  | 30  | 10 | 70 | 50  | 30  | 10 | 70 | 50  | 30 | 10  | 0% |
|                  | 下方光束             |          | 71%  |      | 床  | 10% |     |    |    | 10% |     |    |    | 10% |     |    |    | 10% |    |     |    |
| 室指数              | 照明率 ( X0.01 )    |          |      |      |    |     |     |    |    |     |     |    |    |     |     |    |    |     |    | ZCM |    |
| 保守率              | 良                | 0.63     | 0.6  | 0.6  | 57 | 46  | 39  | 34 | 54 | 44  | 38  | 34 | 49 | 41  | 36  | 32 | 45 | 38  | 34 | 30  | 27 |
|                  | 中                | 0.6      | 0.6  | 0.6  | 66 | 56  | 50  | 45 | 63 | 54  | 48  | 44 | 58 | 50  | 45  | 41 | 52 | 46  | 42 | 39  | 34 |
|                  | 否                | 0.56     | 0.56 | 0.56 | 73 | 64  | 57  | 52 | 69 | 61  | 55  | 51 | 63 | 56  | 52  | 48 | 57 | 52  | 48 | 45  | 40 |
|                  |                  |          |      |      | 78 | 70  | 64  | 59 | 75 | 67  | 62  | 57 | 68 | 62  | 58  | 54 | 62 | 57  | 54 | 51  | 45 |
| 下方投影面積<br>等価発光面積 | c m <sup>2</sup> |          | 1.5  | 82   | 74 | 69  | 64  | 78 | 72 | 66  | 62  | 71 | 66 | 62  | 58  | 65 | 61 | 57  | 55 | 48  |    |
|                  | c m <sup>2</sup> |          | 2.0  | 87   | 81 | 76  | 72  | 83 | 77 | 73  | 69  | 75 | 71 | 68  | 65  | 69 | 65 | 63  | 60 | 53  |    |
|                  | c m <sup>2</sup> |          | 2.5  | 90   | 85 | 80  | 77  | 86 | 81 | 77  | 74  | 78 | 75 | 72  | 69  | 71 | 68 | 66  | 64 | 56  |    |
| 取付高さ             | 器具間隔最大限          |          | 3.0  | 92   | 87 | 83  | 80  | 88 | 84 | 80  | 77  | 80 | 77 | 74  | 72  | 73 | 70 | 68  | 67 | 58  |    |
|                  | 横方向 (A)          | 縦方向 (B)  | 4.0  | 94   | 91 | 88  | 85  | 90 | 87 | 84  | 82  | 82 | 80 | 78  | 76  | 75 | 73 | 72  | 70 | 61  |    |
| H m              | 0.60 H m         | 1.22 H m | 5.0  | 96   | 93 | 90  | 88  | 92 | 89 | 87  | 85  | 84 | 82 | 80  | 78  | 76 | 75 | 73  | 72 | 63  |    |
|                  |                  |          | 7.0  | 98   | 95 | 93  | 92  | 93 | 92 | 90  | 88  | 85 | 84 | 83  | 81  | 78 | 77 | 76  | 75 | 65  |    |
|                  |                  |          | 10.0 | 99   | 97 | 96  | 95  | 95 | 93 | 92  | 91  | 87 | 86 | 85  | 84  | 79 | 78 | 78  | 77 | 67  |    |

