

# 屋内照明器具特性

品番 (品名)	XLGB1112	
光源	LLD2000LCE1 ×1	531.0 lm
管理番号	K0176313(0)DR1	
BZ分類	BZ3	

器具効率	85%	天井	80%				70%				50%				30%				0%		
	上方光束		0%	反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
	下方光束		85%		床	10%				10%				10%				10%			
室指数	照明率 (X0.01)																				ZCM
保守率	良	0.67	0.6	5.6	4.7	4.1	3.8	5.5	4.7	4.1	3.8	5.3	4.6	4.1	3.7	5.1	4.5	4.1	3.7	3.6	
	中	0.63	0.8	6.4	5.6	5.0	4.7	6.3	5.5	5.0	4.6	6.1	5.4	5.0	4.6	5.9	5.3	4.9	4.6	4.5	
	否	0.56	1.0	6.9	6.2	5.7	5.3	6.8	6.1	5.6	5.3	6.6	6.0	5.6	5.2	6.4	5.9	5.5	5.2	5.0	
			0.56	1.25	7.3	6.7	6.2	5.8	7.2	6.6	6.2	5.8	7.0	6.5	6.1	5.8	6.8	6.3	6.0	5.7	5.6
下方投影面積			1.5	7.6	7.0	6.6	6.2	7.5	6.9	6.5	6.2	7.3	6.8	6.4	6.1	7.1	6.7	6.4	6.1	5.9	
			2.0	8.0	7.5	7.1	6.8	7.9	7.4	7.1	6.8	7.6	7.3	7.0	6.7	7.4	7.1	6.9	6.6	6.4	
取付高さ	器具間隔最大限		2.5	8.2	7.8	7.5	7.2	8.1	7.7	7.4	7.1	7.9	7.6	7.3	7.1	7.7	7.4	7.2	7.0	6.8	
	横方向 (A)	縦方向 (B)	3.0	8.4	8.0	7.7	7.5	8.2	7.9	7.7	7.4	8.0	7.8	7.5	7.3	7.8	7.6	7.4	7.2	7.0	
Hm	1.39Hm	1.39Hm	4.0	8.6	8.3	8.0	7.8	8.4	8.2	8.0	7.8	8.2	8.0	7.8	7.7	8.0	7.9	7.7	7.5	7.3	
			5.0	8.7	8.5	8.3	8.1	8.6	8.4	8.2	8.0	8.4	8.2	8.0	7.9	8.2	8.0	7.9	7.8	7.5	
			7.0	8.8	8.7	8.5	8.4	8.7	8.6	8.4	8.3	8.5	8.4	8.3	8.1	8.3	8.2	8.1	8.0	7.8	
			10.0	8.9	8.8	8.7	8.6	8.8	8.7	8.6	8.5	8.6	8.5	8.4	8.3	8.4	8.3	8.3	8.2	8.0	

