

屋内照明器具特性	
品番 (品名)	XLGB1001
光源	LLD2000VCE1 ×1 531.0 lm
管理番号	K0176283 (0) DR1
BZ分類	BZ5/0.7/BZ4/6.0/BZ3

器具効率		87 %	反射率	天井	80 %					70 %					50 %					30 %					0 %	
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
					床	10 %					10 %					10 %					10 %					0 %
						室指数	照明率 ( X0.01 )																			
保守率		良 中 否	0.67	0.6	51	40	34	29	49	40	34	29	47	39	33	29	46	38	33	29	27					
			0.63	0.8	60	50	44	39	58	50	43	39	56	48	43	39	54	47	42	38	37					
			0.56	1.0	66	57	51	46	64	56	50	46	62	55	50	46	60	54	49	45	43					
				1.25	71	63	58	53	70	63	57	53	67	61	56	52	65	60	55	52	50					
下方投影面積		cm <sup>2</sup>	1.5	75	68	62	58	73	67	62	58	71	65	61	57	68	64	60	57	55						
			等価発光面積	cm <sup>2</sup>	2.0	79	74	69	66	78	73	69	65	76	71	68	64	73	70	66	64	62				
取付 高さ	器具間隔最大限		2.5	82	78	74	70	81	77	73	70	79	75	72	69	76	73	71	68	66						
	横方向 ( A ) 縦方向 ( B )		3.0	84	80	77	74	83	79	76	73	81	78	75	72	78	76	73	71	69						
H m	1.28 H m 1.28 H m		4.0	87	84	81	78	86	83	80	78	83	81	79	77	81	79	77	75	73						
			5.0	88	86	83	81	87	85	82	81	85	83	81	79	83	81	79	78	76						
			7.0	90	88	86	85	89	87	85	84	86	85	84	82	84	83	82	81	78						
			10.0	91	90	88	87	90	89	87	86	88	87	86	85	86	85	84	83	81						

