

屋内照明器具特性	
品番 (品名)	XLGB1514
光源	LLD40003CQ1 ×1      845.0 lm
管理番号	K0175669 (1) DR 1
BZ分類	BZ2

器具効率	60%	天井	80%				70%				50%				30%				0%																																							
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%																																							
		床	10%				10%				10%				10%				0%																																							
上方光束	1%	室指数																			照明率 (X0.01)																			ZCM																		
下方光束	59%																																																									
保守率	良	0.67	0.6	4.2	3.6	3.3	3.0	4.1	3.6	3.3	3.0	4.0	3.5	3.2	3.0	3.9	3.5	3.2	3.0	2.9																																						
	中	0.63	0.8	4.7	4.2	3.8	3.6	4.6	4.1	3.8	3.6	4.5	4.1	3.8	3.6	4.3	4.0	3.7	3.5	3.4																																						
	否	0.56	1.0	5.0	4.6	4.2	4.0	4.9	4.5	4.2	4.0	4.8	4.4	4.1	3.9	4.6	4.3	4.1	3.9	3.8																																						
			1.25	5.3	4.9	4.6	4.3	5.2	4.8	4.5	4.3	5.0	4.7	4.5	4.3	4.9	4.6	4.4	4.2	4.1																																						
下方投影面積			cm <sup>2</sup>																																																							
			cm <sup>2</sup>																																																							
取付高さ	器具間隔最大限																																																									
	横方向 (A)	縦方向 (B)																																																								
Hm	1.23Hm	1.23Hm	2.5	5.9	5.6	5.4	5.2	5.8	5.5	5.3	5.2	5.6	5.4	5.2	5.1	5.4	5.3	5.1	5.0	4.8																																						
			3.0	6.0	5.8	5.6	5.4	5.9	5.7	5.5	5.3	5.7	5.5	5.4	5.3	5.5	5.4	5.3	5.2	5.0																																						
			4.0	6.1	5.9	5.8	5.6	6.0	5.8	5.7	5.6	5.8	5.7	5.6	5.5	5.7	5.6	5.5	5.4	5.2																																						
			5.0	6.2	6.0	5.9	5.8	6.1	6.0	5.8	5.7	5.9	5.8	5.7	5.6	5.7	5.7	5.6	5.5	5.3																																						
			7.0	6.3	6.2	6.1	6.0	6.2	6.1	6.0	5.9	6.0	5.9	5.8	5.8	5.8	5.8	5.7	5.6	5.4																																						
			10.0	6.3	6.3	6.2	6.1	6.2	6.2	6.1	6.0	6.1	6.0	6.0	5.9	5.9	5.8	5.8	5.8	5.5																																						

