

屋内照明器具特性

品番 (品名)	XLGB1714	
光源	LLD40003CQ1 ×1	845.0 lm
管理番号	K0175669 (1) DR1	
BZ分類	BZ2	

器具効率	60%	天井	80%				70%				50%				30%				0%				
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%				
上方光束	1%	床	10%				10%				10%				10%				0%				
下方光束	59%	室指数	照明率 (×0.01)																				ZCM
保守率	良	0.67	0.6	4.2	3.6	3.3	3.0	4.1	3.6	3.3	3.0	4.0	3.5	3.2	3.0	3.9	3.5	3.2	3.0	2.9			
	中	0.63	0.8	4.7	4.2	3.8	3.6	4.6	4.1	3.8	3.6	4.5	4.1	3.8	3.6	4.3	4.0	3.7	3.5	3.4			
	否	0.56	1.0	5.0	4.6	4.2	4.0	4.9	4.5	4.2	4.0	4.8	4.4	4.1	3.9	4.6	4.3	4.1	3.9	3.8			
			1.25	5.3	4.9	4.6	4.3	5.2	4.8	4.5	4.3	5.0	4.7	4.5	4.3	4.9	4.6	4.4	4.2	4.1			
下方投影面積		cm ²	1.5	5.5	5.1	4.8	4.6	5.4	5.1	4.8	4.6	5.2	4.9	4.7	4.5	5.1	4.8	4.6	4.5	4.3			
等価発光面積		cm ²	2.0	5.7	5.4	5.2	5.0	5.6	5.4	5.1	4.9	5.5	5.2	5.0	4.9	5.3	5.1	4.9	4.8	4.6			
取付高さ	器具間隔最大限		2.5	5.9	5.6	5.4	5.2	5.8	5.5	5.3	5.2	5.6	5.4	5.2	5.1	5.4	5.3	5.1	5.0	4.8			
	横方向 (A)	縦方向 (B)	3.0	6.0	5.8	5.6	5.4	5.9	5.7	5.5	5.3	5.7	5.5	5.4	5.3	5.5	5.4	5.3	5.2	5.0			
Hm	1.23Hm	1.23Hm	4.0	6.1	5.9	5.8	5.6	6.0	5.8	5.7	5.6	5.8	5.7	5.6	5.5	5.7	5.6	5.5	5.4	5.2			
			5.0	6.2	6.0	5.9	5.8	6.1	6.0	5.8	5.7	5.9	5.8	5.7	5.6	5.7	5.7	5.6	5.5	5.3			
			7.0	6.3	6.2	6.1	6.0	6.2	6.1	6.0	5.9	6.0	5.9	5.8	5.8	5.8	5.8	5.7	5.6	5.4			
			10.0	6.3	6.3	6.2	6.1	6.2	6.2	6.1	6.0	6.1	6.0	6.0	5.9	5.9	5.8	5.8	5.8	5.5			

