

屋内照明器具特性

品番 (品名)	XLH1560DW	
光源	LED4000_85_1350 ×1 1350.0lm	
管理番号	K0173386(0)DB1	
BZ分類	BZ1	

器具効率	100%	天井	80%				70%				50%				30%				0%	
	上方光束 0%		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
下方光束	100%	床		10%				10%				10%				10%				0%
室指数	照明率 (X0.01)																			ZCM
保守率	良 0.77	0.6	87	81	78	75	86	81	78	75	85	80	77	75	84	80	77	75	74	
	中 0.72		0.8	92	88	84	82	92	87	84	82	90	86	84	82	89	86	83	81	80
	否 0.68		1.0	96	91	88	86	95	91	88	86	93	90	88	86	92	89	87	85	84
下方投影面積	cm ²	1.25	98	95	92	90	97	94	92	90	96	93	91	89	94	92	90	89	87	
		1.5	100	97	94	92	99	96	94	92	97	95	93	91	96	94	92	91	89	
等価発光面積	cm ²	2.0	102	100	98	96	101	99	97	95	100	98	96	95	98	96	95	94	92	
		2.5	104	101	100	98	103	101	99	98	101	99	98	96	99	98	96	95	94	
器具間隔最大限	高さ		3.0	104	103	101	100	103	102	100	99	101	100	99	98	100	99	98	97	95
	横方向 (A)	縦方向 (B)																		
Hm	0.39Hm	0.70Hm	4.0	105	104	103	102	104	103	102	101	102	101	100	101	100	100	99	98	96
			5.0	106	105	104	103	105	104	103	102	103	102	101	101	101	100	100	99	97
			7.0	107	106	105	105	106	105	104	104	103	103	102	102	101	101	100	98	
			10.0	107	107	106	106	106	105	105	104	104	103	103	102	102	102	101	99	

