

屋内照明器具特性

品番 (品名)	S P L 5 4 2 7														
光源	LLD4000LCE1 ×4 845.0 l m														
管理番号	K0176038 (0) DR 1														
B Z 分類	B Z 5														

器具効率	91 %	天井	80 %				70 %				50 %				30 %				0 %		
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
上方光束	0 %	室指数	照明率 (X0.01)																Z C M		
下方光束	91 %																				
保守率	良 中 否 0.67 0.63 0.56	0.6	52	41	34	29	51	40	34	29	49	39	33	29	47	38	33	29	27		
		0.8	61	51	44	39	60	50	43	38	57	49	43	38	55	48	42	38	36		
		1.0	67	58	51	45	66	57	50	45	63	55	50	45	61	54	49	45	43		
		1.25	73	64	58	52	71	63	57	52	69	62	56	52	66	60	55	51	49		
下方投影面積	c m ²	1.5	77	69	63	58	75	68	62	57	72	66	61	57	70	64	60	56	54		
		2.0	82	75	70	65	80	74	69	65	78	72	68	64	75	71	67	63	61		
取付高さ	器具間隔最大限		2.5	85	79	75	71	84	78	74	70	81	76	73	69	78	75	71	68	66	
	横方向 (A)	縦方向 (B)	3.0	87	82	78	74	86	81	77	74	83	79	76	73	81	77	75	72	70	
H m	1.28 H m	1.27 H m	4.0	90	86	83	80	89	85	82	79	86	83	80	78	84	81	79	77	74	
			5.0	92	89	86	83	91	88	85	82	88	86	83	81	86	84	82	80	77	
			7.0	94	91	89	87	93	90	88	86	90	88	87	85	88	86	85	84	81	
			10.0	95	94	92	90	94	93	91	90	92	91	89	88	90	89	87	86	84	

