

# 屋内照明器具特性

品番 (品名)	S P L 5 4 2 7	
光源	LLD2020LCE1 x4	460.0 l m
管理番号	K0176041 ( 0 ) DR 1	
B Z 分類	B Z 1	

器具効率	93 %	天井	80 %				70 %				50 %				30 %				0 %	
	上方光束 0 %		反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
下方光束	93 %	床		10 %				10 %				10 %				10 %				0 %
室指数	照明率 ( X 0 . 0 1 )																			Z C M
保守率	良	0.67	0.6	77	71	67	65	76	71	67	65	75	70	67	65	74	70	67	64	63
	中	0.63	0.8	83	77	74	71	82	77	74	71	80	76	73	71	79	75	73	71	69
	否	0.56	1.0	86	82	78	75	85	81	78	75	84	80	77	75	82	79	77	75	73
下方投影面積	等価発光面積	c m <sup>2</sup>	1.25	89	85	82	79	88	84	82	79	87	83	81	79	85	82	80	78	77
			1.5	91	88	85	82	90	87	84	82	89	86	83	81	87	85	82	81	79
取付高さ	器具間隔最大限		2.0	94	91	88	86	93	90	88	86	91	89	87	85	89	87	86	84	83
	横方向 ( A )	縦方向 ( B )	2.5	95	93	91	89	94	92	90	88	92	90	89	87	91	89	88	86	85
H m	0.41 H m	0.40 H m	3.0	96	94	92	91	95	93	92	90	93	92	90	89	92	90	89	88	86
			4.0	98	96	94	93	97	95	94	92	95	93	92	91	93	92	91	90	88
			5.0	98	97	96	94	97	96	95	94	95	94	93	92	93	92	92	91	89
			7.0	99	98	97	96	98	97	96	95	96	95	95	94	94	93	93	92	90
			10.0	100	99	98	98	99	98	97	97	97	96	96	95	95	94	94	93	91

