

# 屋内照明器具特性

品番 (品名)	LGB15132WF	
光源	LDA7L-D-G/S/Z6 ×1	810.0 lm
管理番号	K0172591(0)DB1	
BZ分類	BZ5	

器具効率	46%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	0%	床	10%				10%				10%				10%				0%	
下方光束	46%	室指数	照明率 ( X0.01 )																ZCM	
保守率	良 中 否 0.63 0.6 0.56	0.6	2.6	2.1	1.7	1.4	2.6	2.0	1.7	1.4	2.4	2.0	1.7	1.4	2.3	1.9	1.6	1.4	1.3	
		0.8	3.1	2.6	2.2	1.9	3.0	2.5	2.2	1.9	2.9	2.5	2.1	1.9	2.8	2.4	2.1	1.9	1.8	
		1.0	3.4	2.9	2.5	2.3	3.3	2.9	2.5	2.3	3.2	2.8	2.5	2.3	3.1	2.7	2.5	2.2	2.1	
		1.25	3.7	3.2	2.9	2.6	3.6	3.2	2.9	2.6	3.4	3.1	2.8	2.6	3.3	3.0	2.8	2.6	2.5	
下方投影面積	cm <sup>2</sup>	1.5	3.9	3.5	3.1	2.9	3.8	3.4	3.1	2.9	3.6	3.3	3.1	2.8	3.5	3.2	3.0	2.8	2.7	
		2.0	4.1	3.8	3.5	3.3	4.0	3.7	3.5	3.3	3.9	3.6	3.4	3.2	3.8	3.5	3.4	3.2	3.1	
取付高さ	器具間隔最大限		2.5	4.3	4.0	3.7	3.5	4.2	3.9	3.7	3.5	4.1	3.8	3.6	3.5	3.9	3.7	3.6	3.4	3.3
	横方向 (A)	縦方向 (B)	3.0	4.4	4.1	3.9	3.7	4.3	4.1	3.9	3.7	4.2	4.0	3.8	3.7	4.1	3.9	3.7	3.6	3.5
Hm	1.26Hm	1.26Hm	4.0	4.5	4.3	4.2	4.0	4.5	4.3	4.1	4.0	4.3	4.2	4.0	3.9	4.2	4.1	4.0	3.9	3.7
			5.0	4.6	4.5	4.3	4.2	4.5	4.4	4.3	4.1	4.4	4.3	4.2	4.1	4.3	4.2	4.1	4.0	3.9
			7.0	4.7	4.6	4.5	4.4	4.6	4.5	4.4	4.3	4.5	4.4	4.3	4.3	4.4	4.3	4.3	4.2	4.1
			10.0	4.8	4.7	4.6	4.5	4.7	4.6	4.6	4.5	4.6	4.5	4.5	4.4	4.5	4.4	4.4	4.3	4.2

