

屋内照明器具特性

品番 (品名)	S C 8 0 1 B F	
光源	LDA5 L - D - G - E17 / S / Z4 x1	440.0 l m
管理番号	K0131311 (0) DR 1	
B Z 分類	BZ10 / 0.7 / BZ9 / 1.8 / BZ10 / 2.3 / BZ9 / 2.8 / BZ1	

器具効率	86 %	天井	80 %				70 %				50 %				30 %				0 %	
	上方光束		52 %	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
下方光束	34 %	床	10 %				10 %				10 %				10 %				0 %	
室指数			照明率 (X0.01)																Z C M	
保守率	良	0.63	0.6	37	27	20	16	34	24	18	14	26	19	15	11	20	15	11	8	3
	中	0.6	0.6	44	34	27	22	40	31	24	20	31	24	19	16	24	18	15	12	5
	否	0.56	1.0	49	39	32	27	44	35	29	24	35	28	23	19	26	21	18	15	7
下方投影面積	等価発光面積	cm ²	1.25	54	44	37	32	48	40	34	29	38	32	27	23	29	24	21	18	9
			1.5	57	49	42	36	52	44	38	33	41	35	30	27	31	27	23	20	10
取付高さ	器具間隔最大限		2.5	65	58	53	48	59	53	48	44	47	43	39	35	36	33	30	27	15
	横方向 (A)	縦方向 (B)	3.0	67	61	56	51	61	56	51	47	49	45	41	38	38	35	32	30	17
H m	0.00H m	0.00H m	4.0	70	65	61	57	64	59	55	52	52	48	45	42	40	38	35	33	19
			5.0	72	68	64	60	66	62	58	55	53	50	48	45	42	39	37	36	21
			7.0	75	71	68	65	68	65	62	60	55	53	51	49	44	42	40	39	23
			10.0	76	74	71	69	70	68	65	63	57	55	54	52	45	44	43	41	26

