

屋内照明器具特性	
品番 (品名)	LGWC85012U
光源	LDA5L-D-G-E17/S/Z4 ×1 440.0 1 m
管理番号	K0188013(0)DB1
BZ分類	BZ7

器具効率	62%	天井	80%				70%				50%				30%				0%				
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%				
上方光束	36%	床	10%				10%				10%				10%				0%				
下方光束	26%	室指数	照明率 (X0.01)																				ZCM
保守率	良	0.63	0.6	2.8	2.1	1.6	1.3	2.6	1.9	1.5	1.2	2.1	1.6	1.2	1.0	1.6	1.2	1.0	0.8	0.4			
	中	0.6	0.8	3.3	2.6	2.1	1.8	3.0	2.4	2.0	1.6	2.4	2.0	1.6	1.4	1.9	1.6	1.3	1.1	0.6			
	否	0.56	1.0	3.7	3.0	2.5	2.2	3.4	2.8	2.3	2.0	2.7	2.3	1.9	1.7	2.1	1.8	1.5	1.3	0.8			
			1.25	4.0	3.4	2.9	2.6	3.7	3.1	2.7	2.4	3.0	2.6	2.2	2.0	2.3	2.0	1.8	1.6	1.0			
下方投影面積		cm ²	1.5	4.3	3.7	3.2	2.9	3.9	3.4	3.0	2.7	3.2	2.8	2.5	2.2	2.5	2.2	2.0	1.8	1.1			
等価発光面積		cm ²	2.0	4.6	4.1	3.7	3.4	4.2	3.8	3.4	3.1	3.4	3.1	2.8	2.6	2.7	2.5	2.3	2.1	1.3			
取付高さ	器具間隔最大限		2.5	4.8	4.4	4.0	3.7	4.4	4.0	3.7	3.4	3.6	3.3	3.1	2.9	2.9	2.7	2.5	2.3	1.5			
	横方向 (A)	縦方向 (B)	3.0	5.0	4.6	4.3	4.0	4.6	4.2	3.9	3.7	3.7	3.5	3.3	3.1	3.0	2.8	2.6	2.5	1.6			
1.5m	2.6m	2m	4.0	5.2	4.9	4.6	4.3	4.8	4.5	4.2	4.0	3.9	3.7	3.5	3.3	3.1	3.0	2.8	2.7	1.7			
2	3.46	2.65	5.0	5.3	5.0	4.8	4.6	4.9	4.6	4.4	4.2	4.0	3.8	3.7	3.5	3.2	3.1	3.0	2.9	1.9			
2.5	4.3	3.28	7.0	5.5	5.3	5.1	4.9	5.0	4.8	4.7	4.5	4.2	4.0	3.9	3.8	3.4	3.3	3.2	3.1	2.0			
3	5.16	3.94	10.0	5.6	5.4	5.3	5.1	5.1	5.0	4.9	4.7	4.3	4.2	4.1	4.0	3.5	3.4	3.3	3.2	2.1			

