

屋内照明器具特性	
品番 (品名)	LGB57490K
光源	LDA7L-D-G/S/Z6 ×4 810.0 lm
管理番号	K0166333 (0) DB1
BZ分類	BZ6

器具効率		89 %	反射率	天井	80 %				70 %				50 %				30 %				0 %	
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
					床	10 %				10 %				10 %				10 %				0 %
						室指数	照明率 ( X0.01 ) ZCM															
保守率		良 中 否	0.67	0.6	45	34	27	23	42	32	26	22	37	29	24	20	32	26	22	18	15	
			0.63	0.8	52	42	35	30	49	40	33	29	43	36	30	26	38	32	27	24	19	
			0.56	1.0	58	48	41	35	54	45	39	34	47	40	35	31	41	36	32	28	23	
				1.25	62	53	46	41	58	50	44	39	51	45	40	36	45	40	36	32	26	
下方投影面積		cm <sup>2</sup>	1.5	66	57	51	45	62	54	48	43	54	48	44	40	48	43	39	36	29		
等価発光面積			cm <sup>2</sup>	2.0	70	63	57	52	66	60	54	50	58	53	49	45	51	47	44	41	33	
取付 高さ	器具間隔最大限			2.5	73	67	62	57	69	63	59	54	61	57	53	49	54	50	47	44	36	
	横方向 ( A ) 縦方向 ( B )			3.0	76	70	65	61	71	66	62	58	63	59	56	52	56	52	50	47	38	
H m	1.37 H m	1.36 H m		4.0	78	74	70	66	74	70	66	63	66	63	59	57	58	55	53	51	42	
			5.0	80	76	73	69	76	72	69	66	68	65	62	60	60	58	55	53	44		
			7.0	82	79	76	74	78	75	73	70	70	67	65	63	62	60	58	57	47		
			10.0	84	82	80	77	80	78	76	74	72	70	68	67	64	62	61	60	49		

