

屋内照明器具特性	
品番 (品名)	L G W C 8 1 3 1 0 K
光源	LED2700_70_243 x1 243.0 l m
管理番号	K0149622(0)DR1
BZ分類	BZ9

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %																																	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %																																	
		床	10 %				10 %				10 %				10 %				0 %																																	
上方光束	50 %	室指数																	照明率 (X0.01)																	Z C M																
下方光束	50 %																																																			
保守率	良 中 否	0.63	0.6	0.56	0.6	44	31	23	17	40	29	21	16	33	24	18	13	26	19	14	10	5																														
		0.6	0.8	52	39	31	25	47	36	28	23	39	30	24	19	31	24	19	15	8																																
		1.0	1.0	58	46	37	30	53	42	34	28	43	35	28	23	34	28	23	19	11																																
		0.56	1.25	63	52	43	37	58	48	40	34	47	39	33	28	38	32	27	23	14																																
下方投影面積	c m ²	1.5	67	57	48	42	61	52	45	39	50	43	37	32	40	35	30	26	16																																	
		2.0	73	64	56	50	67	58	52	46	55	49	43	39	44	39	35	31	20																																	
取付高さ	器具間隔最大限		2.5	77	68	61	55	70	63	57	51	58	53	48	43	47	43	39	35	23																																
	横方向 (A)	縦方向 (B)	3.0	79	72	65	60	73	66	60	55	61	55	51	47	49	45	42	38	25																																
H m	1.38 H m	1.30 H m	4.0	83	77	71	66	76	71	66	61	64	60	56	52	52	49	46	43	29																																
			5.0	85	80	75	70	79	74	69	65	66	62	59	56	54	51	49	46	31																																
			7.0	88	84	80	76	82	78	74	71	69	66	63	60	57	54	52	50	35																																
			10.0	90	87	84	81	84	81	78	75	71	69	67	64	59	57	55	54	38																																

