

屋内照明器具特性

品番 (品名)	LGWJ 56001U																
光源	LDA5L-D-G-E17/S/Z4 ×1 440.0 l m																
管理番号	K0188012(0)DB1																
BZ分類	BZ9/0.9/BZ8/4.5/BZ7																

器具効率	23%	天井	80%				70%				50%				30%				0%	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
上方光束	5%	反射率	10%				10%				10%				10%				0%	
下方光束	18%		床	10%				10%				10%				10%				0%
		室指数	照明率 (X0.01) ZCM																	
保守率	良	0.63	0.6	10	7	5	4	10	7	5	3	9	6	4	3	8	5	4	3	2
	中	0.6	0.8	12	9	7	5	12	9	7	5	10	8	6	5	9	7	6	4	3
	否	0.56	1.0	14	11	9	7	13	10	8	7	12	9	8	6	10	8	7	6	4
			1.25	15	12	10	8	14	12	10	8	13	11	9	8	11	10	8	7	6
下方投影面積	cm ²		1.5	16	14	11	10	15	13	11	9	14	12	10	9	12	11	9	8	7
等価発光面積	cm ²		2.0	18	15	13	12	17	15	13	11	15	13	12	11	14	12	11	10	8
取付高さ	器具間隔最大限		2.5	19	17	15	13	18	16	14	13	16	15	13	12	15	13	12	11	9
	横方向 (A)	縦方向 (B)	3.0	19	18	16	14	19	17	15	14	17	15	14	13	15	14	13	12	10
Hm	0.00Hm	0.00Hm	4.0	20	19	17	16	19	18	17	16	18	17	15	14	16	15	14	13	12
			5.0	21	20	18	17	20	19	18	17	18	17	16	15	17	16	15	14	12
			7.0	22	21	20	19	21	20	19	18	19	18	18	17	17	17	16	16	14
			10.0	22	21	21	20	21	21	20	19	20	19	19	18	18	18	17	17	15

