

屋内照明器具特性

品番 (品名)	L G W 8 0 3 1 5 K														
光源	LED2700_70_300 ×1 300.0 l m														
管理番号	K0146950 (0) DB 1														
B Z 分類	B Z 6														

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %			
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
				床	10 %				10 %				10 %				10 %				0 %	
上方光束	28 %	室指数	照明率 (X 0.01)																			Z C M
下方光束	72 %																					
保守率	良 中 否 0.63 0.6 0.56	0.6	4.9	3.7	2.8	2.3	4.6	3.5	2.7	2.2	4.1	3.2	2.5	2.0	3.6	2.8	2.3	1.9	1.5			
		0.8	5.8	4.6	3.7	3.1	5.5	4.4	3.6	3.0	4.9	3.9	3.3	2.8	4.3	3.6	3.0	2.6	2.1			
		1.0	6.4	5.2	4.4	3.8	6.1	5.0	4.2	3.6	5.4	4.5	3.9	3.4	4.8	4.1	3.5	3.1	2.5			
		1.25	7.0	5.9	5.1	4.4	6.6	5.6	4.9	4.3	5.9	5.1	4.4	3.9	5.2	4.6	4.0	3.6	3.0			
下方投影面積	c m ²	1.5	7.4	6.4	5.6	5.0	7.0	6.1	5.3	4.8	6.2	5.5	4.9	4.4	5.5	4.9	4.4	4.0	3.3			
		2.0	7.9	7.1	6.3	5.7	7.5	6.7	6.1	5.5	6.7	6.1	5.5	5.1	6.0	5.5	5.0	4.6	3.9			
取付高さ	器具間隔最大限		2.5	8.3	7.5	6.9	6.3	7.9	7.2	6.6	6.0	7.0	6.5	6.0	5.6	6.3	5.8	5.4	4.3			
	横方向 (A)	縦方向 (B)	3.0	8.5	7.8	7.2	6.7	8.1	7.5	6.9	6.5	7.3	6.8	6.3	5.9	6.5	6.1	5.7	4.6			
H m	1.40 H m	1.40 H m	4.0	8.9	8.3	7.8	7.3	8.5	7.9	7.5	7.0	7.6	7.2	6.8	6.5	6.8	6.5	6.2	5.0			
			5.0	9.1	8.6	8.2	7.7	8.7	8.2	7.8	7.4	7.8	7.5	7.1	6.8	7.0	6.8	6.5	5.3			
			7.0	9.4	9.0	8.6	8.3	8.9	8.6	8.3	7.9	8.1	7.8	7.5	7.3	7.3	7.1	6.9	5.7			
			10.0	9.6	9.3	9.0	8.7	9.2	8.9	8.6	8.4	8.3	8.1	7.9	7.7	7.5	7.4	7.2	6.0			

