

# 屋内照明器具特性

品番 (品名)	L G W 8 0 3 3 6 K									
光源	LED5000_70_329 x1					329.0 l m				
管理番号	K0146950(0)DB1									
BZ分類	BZ6									

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %																																				
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %																																				
		床	10 %				10 %				10 %				10 %				0 %																																				
上方光束	28 %	室指数																		照明率 ( X0.01)																		ZCM																	
下方光束	72 %																																																						
保守率	良 中 否	0.63	0.6	0.8	1.0	1.25	1.5	2.0	2.5	3.0	4.0	5.0	7.0	10.0	4.9	3.7	2.8	2.3	4.6	3.5	2.7	2.2	4.1	3.2	2.5	2.0	3.6	2.8	2.3	1.9	1.5																								
		0.6	0.8	1.0	1.25	1.5	2.0	2.5	3.0	4.0	5.0	7.0	10.0	5.8	4.6	3.7	3.1	5.5	4.4	3.6	3.0	4.9	3.9	3.3	2.8	4.3	3.6	3.0	2.6	2.1																									
		0.56	0.8	1.0	1.25	1.5	2.0	2.5	3.0	4.0	5.0	7.0	10.0	6.4	5.2	4.4	3.8	6.1	5.0	4.2	3.6	5.4	4.5	3.9	3.4	4.8	4.1	3.5	3.1	2.5																									
		0.56	0.8	1.0	1.25	1.5	2.0	2.5	3.0	4.0	5.0	7.0	10.0	7.0	5.9	5.1	4.4	6.6	5.6	4.9	4.3	5.9	5.1	4.4	3.9	5.2	4.6	4.0	3.6	3.0																									
下方投影面積	c m <sup>2</sup>	1.5	7.4	6.4	5.6	5.0	7.0	6.1	5.3	4.8	6.2	5.5	4.9	4.4	5.5	4.9	4.4	4.0	3.6	3.0																																			
		2.0	7.9	7.1	6.3	5.7	7.5	6.7	6.1	5.5	6.7	6.1	5.5	5.1	6.0	5.5	5.0	4.6	4.0	3.3																																			
取付高さ	器具間隔最大限		2.5	8.3	7.5	6.9	6.3	7.9	7.2	6.6	6.0	7.0	6.5	6.0	5.6	6.3	5.8	5.4	5.1	4.3																																			
	横方向 (A)	縦方向 (B)	3.0	8.5	7.8	7.2	6.7	8.1	7.5	6.9	6.5	7.3	6.8	6.3	5.9	6.5	6.1	5.7	5.4	4.6																																			
H m	1.40 H m	1.40 H m	4.0	8.9	8.3	7.8	7.3	8.5	7.9	7.5	7.0	7.6	7.2	6.8	6.5	6.8	6.5	6.2	5.9	5.0																																			
			5.0	9.1	8.6	8.2	7.7	8.7	8.2	7.8	7.4	7.8	7.5	7.1	6.8	7.0	6.8	6.5	6.2	5.3																																			
			7.0	9.4	9.0	8.6	8.3	8.9	8.6	8.3	7.9	8.1	7.8	7.5	7.3	7.3	7.1	6.9	6.7	5.7																																			
			10.0	9.6	9.3	9.0	8.7	9.2	8.9	8.6	8.4	8.3	8.1	7.9	7.7	7.5	7.4	7.2	7.0	6.0																																			

